



No.	DESCRIPTION	MATERIAL
1	KEY	CAST LOW LEAD BRASS ALLOY
2	BODY	CAST LOW LEAD BRASS ALLOY
3	KEY INSERT	CYCOLAC ABS PLASTIC
4	O-RING	ASTM D2000 RUBBER
5	O-RING	ASTM D2000 RUBBER
6	TOP SEAL	ASTM D2000 RUBBER
7	RETAINING RING	BRONZE ASTM B103 ALLOY C52100
8	THRUST WASHER	CELCON M90 CF-2001

SIZE	A	B	C
3/4"	3.438	1.935	3.178
1"	4.156	2.278	3.719

ALL WETTED PARTS ARE LOW LEAD BRASS ALLOY

FILEPATH: PROD-ENG\MUELLER\APPROVED\H15515N

DWG NUMBER
H1500 1N
442-MRKTG

TITLE TO AND OWNERSHIP OF THIS ENGINEERING DATA REMAINS IN Mueller Co. NO USE IS TO BE MADE OF THIS DATA EXCEPT AS SPECIFICALLY AUTHORIZED BY Mueller Co. ASSENT ON THE PART OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED.

DRFTR	RWB	9/2/15	Mueller Co.		
CHKR					
ENGR					
MGR					
			UNLESS OTHERWISE NOTED	THIRD ANGLE PROJECTION	
			SURFACE PREPARATION:		
			BREAK CORNER(S) ---- .000		
			SURFACE FINISH -- 000 RMS	REF. No.	
			TOLERANCE(S):	SCALE	
			LINEAR ----- ± .000	NONE	
			ANGULAR ----- ± 0°00'		
			STK No:		
			MAT'L:		
			DESCR.	DWG NUMBER	
			ORISEAL III LLB CURB VALVE	H1500 1N	
			(FIP x FIP)		
REV	ECR	DESCRIPTION	DATE	BY	CHKR
PER EST NO: DXXXX EST FIN WT = 0.0000 lbs					