



No.	DESCRIPTION	MATERIAL
1	BODY	CAST LOW LEAD BRASS ALLOY
2	KEY	CAST LOW LEAD BRASS ALLOY
3	KEY INSERT	ABS CYCOLAC MG47N PLASTIC
4	TUBE NUT	CAST BRASS ASTM B62 ALLOY C83600
5	TOP SEAL	RUBBER
6	RETAINING RING	BRONZE ASTM B103 ALLOY C52100
7	THRUST WASHER	CELCON M90 PLASTIC
8	O-RING	RUBBER ASTM D-2000 EPDM
9	O-RING	RUBBER ASTM D-2000 EPDM

SIZE	A	B	C
3/4	4.66	1.94	3.18
1	5.41	2.16	3.60

NOTE: ALL WETTED PARTS ARE LOW LEAD BRASS ALLOY

FILEPATH: PROD-ENG\MUELLER\ASYSUBMITTALS\H1502-2N

DRFTR	RWB	4/16/14			
CHKR					
ENGR					
MGR					
			UNLESS OTHERWISE NOTED	THIRD ANGLE PROJECTION	
			SURFACE PREPARATION:		
			BREAK CORNER(S) ---- .000		
			SURFACE FINISH -- XX RMS	REF. No.	
			TOLERANCE(S):	SCALE	
			LINEAR ----- ± .000	NONE	
			ANGULAR ----- ± 0°00'		
			STK No:		
			MAT'L:		
			DESCR.		
			DRISEAL III LLB CURB VALVE	DWG NUMBER	
			(CS x CS)	H1502-2N	
REV	ECR	DESCRIPTION	DATE	BY	CHKR
PER EST NO: DXXXX EST FIN WT = 0.0000 lbs					

DWG NUMBER  
H1502-2N  
442-MRKTG

TITLE TO AND OWNERSHIP OF THIS ENGINEERING DATA REMAINS IN Mueller Co. NO USE IS TO BE MADE OF THIS DATA EXCEPT AS SPECIFICALLY AUTHORIZED BY Mueller Co. ASSENT ON THE PART OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED