



UL 789 LISTED, ASSEMBLED IN THE UNITED STATES

POST INDICATOR PAINT SPEC:

WRENCH: Purchased with one coat of black primer and Mueller applies one coat of Mueller Red Sherwin Williams Kem 400.
 CENTER BARREL/UPPER BARREL: One coat of Sherwin Williams Universal Primer—orange rust primer and one coat of Mueller Red Sherwin Williams Kem 400.
 BELL: One coat of Sherwin Williams 70P water reduced black primer.
 POST HEAD & COVER: One coat of Sherwin Williams 70P water reduced black primer and one coat of Mueller Red Sherwin Williams Kem 400.

| ITEM NO. | PART NO. | CAT. PART NO. | DESCRIPTION | MATERIAL | MATERIAL STANDARD |
|----------|----------|---------------|-------------------------|-------------------|-----------------------|
| 1 | 290553 | P206 | SHUT TARGET | PLASTIC | ZITEL |
| 2 | 290552 | P209 | OPEN TARGET | PLASTIC | ZITEL |
| 3 | 290154 | P217 | COTTER PIN (SHORT) | BRASS | ASTM B21 |
| 4 | 290155 | P218 | COUPLING | STEEL | ASTM A500 GR.B |
| 5 | 290154 | P219 | COTTER PIN (LONG) | BRASS | ASTM B21 |
| 6 | 290157 | P242 | RETAINING RING | STAINLESS STEEL | ANSI 302 |
| 7 | 290191 | P244 | HEX BOLT | STEEL/ZINC PLATED | ASTM A307 GR.A |
| 8 | 148689 | P273 | BELL | CAST IRON | ASTM A126 CL.B |
| 9 | 190939 | P303 | HEX NUT | STEEL/ZINC PLATED | ASTM A563 GR.A |
| 10 | 148691-1 | P304 | OPERATING NUT | DUCTILE IRON | ASTM A536 GR.65-45-12 |
| 11 | 290143 | P305 | CAP | POLYPROPYLENE | |
| 12 | 190330 | P307 | SPRING PIN | STAINLESS STEEL | ALLOY 420 |
| 13 | 241011 | P308 | THREADED SLEEVE | ALUMINUM | ALLOY 319 |
| 14 | 148653 | P309 | UPPER STEM | STEEL | ASTM A513 |
| 15 | 198582 | P315 | PIPE PLUG -- HEX SOCKET | STEEL | |
| 16 | 148692 | P316 | POST HEAD | CAST IRON | ASTM A126 CL.B |
| 17 | 148790 | P317 | WINDOW | MOLDED PLASTIC | |
| 18 | 190560 | P322 | HEX HEAD SCREW | STEEL/ZINC PLATED | ASTM A307 GR.A |
| 19 | 148760 | P323 | LOWER BARREL | PVC | DR14 UL LISTED |
| 20 | 147307 | P324 | UPPER BARREL | STEEL | ASTM A53 GR.B |
| 21 | 148690-1 | P325 | WRENCH | STEEL | ASTM A36 H.R.S. |
| 22 | 290137 | P326 | LOWER STEM | STEEL | ASTM A500 GR.B |
| 23 | 198428 | P329 | SOCKET HEAD SET SCREW | STEEL | ANSI B18.3 |
| 24 | 290156 | P350 | COUPLING INSERT | STEEL | ASTM A500 GR.B |
| 25 | 290164 | P352 | SHIPPING DISC * | PRESS BOARD | |

* ITEMS NOT SHOWN

| REV. | DESCRIPTION | REF. | DRFTS | CHK'R | APP | DATE |
|------|--|---------|-------|-------|-----|---------|
| C | ADD PART NUMBERS TO CHART | | ANC | | | 7-22-11 |
| B | ADD PAINT SPEC | | ANC | | | 7-12-11 |
| A | CHANGE WRENCH FROM DUCTILE IRON TO STEEL, RENOSD ITEM# 19 MATERIAL | EO 3209 | ANC | MDW | MDW | 4-19-11 |

CATALOG NUMBER
A20807-1044LWA SHOWN

| | | | | | |
|---------------------------------------|--------------------------|--|------------------------|-------------------------------|---------------|
| <p>Mueller Red</p> | | <p>TOLERANCES -- MACHINING UNLESS OTHERWISE NOTED</p> | | <p>THIRD ANGLE PROJECTION</p> | |
| <p>INITIAL RELEASE</p> | <p>DRFTS ANC 4-12-11</p> | <p>BREAK EDGES</p> | <p>MACH. .006/.016</p> | <p>FINISH</p> | <p>SCALE</p> |
| <p>CHK'R MDW 4-12-11</p> | <p>APP MDW 4-12-11</p> | <p>FRACTIONS DECIMALS 1/16 2 PL ±.010</p> | <p>ANGLES 1/2°</p> | <p>REF. NO. 1-4</p> | <p>FINISH</p> |
| <p>E.O. NUMBER EO 3181-2</p> | | <p>MAT'L 16"-24" VERTICAL DESCR. ADJUSTABLE INDICATOR POST</p> | | <p>REVISION C</p> | |
| <p>ASSEMBLY WITH PVC LOWER BARREL</p> | | <p>NUMBER A20807</p> | | <p>SHEET 1 OF 1</p> | |