



No.	DESCRIPTION	MATERIAL
1	STEM	LOW LEAD BRASS ALLOY
2	O-RING	EPDM D2000
3	BALL	LOW LEAD BRASS ALLOY
4	GASKET - SEAL	NITRILE D2000
5	BODY	CAST LOW LEAD BRASS ALLOY
6	O-RING	EPDM D2000
7	END PIECE	CAST LOW LEAD BRASS ALLOY
8	CAP	CAST BRASS ASTM B62 ALLOY C83600
9	SOLID PIN	AISI 303 STAINLEES STEEL
10	LEVER HANDLE	CAST BRASS ASTM B62 ALLOY C83600
11	ROLLPIN	AISI 420 STAINLEES STEEL

SIZE	ØA	B	C	D	E	F
3/4	.750	3.070	.840	2.323	3.163	3.66
1	1.000	3.972	1.150	2.567	3.717	
1-1/2	1.500	4.134	1.500	3.372	4.872	4.25
2	2.000	4.940	1.820	3.919	5.739	

FILEPATH: PROD-ENG\MUELLER\ASYSUBMITTALS\B2028303N

DRFTR	JGarvin	8/5/11			UNLESS OTHERWISE NOTED SURFACE PREPARATION: BREAK CORNER(S) ---- .000 SURFACE FINISH -- XX RMS TOLERANCE(S): LINEAR ----- ± .000 ANGULAR ----- ± 0°00'		THIRD ANGLE PROJECTION REF. No. SCALE NONE	
CHKR								
ENGR								
MGR								
BY DATE			STK No:		MAT'L:		DESCR.	
					DESCR.		DWG NUMBER	
					INLINE CURB BALL VALVE LOW LEAD BRASS -WITH HANDLE-(FIP x FIP)		B2028303N	
REV	ECR	DESCRIPTION	DATE	BY	CHKR	PER EST NO: DXXXX EST FIN WT = 0.0000 lbs		

DWG NUMBER
B2028303N
442-MRKTG

TITLE TO AND OWNERSHIP OF THIS ENGINEERING DATA REMAINS IN Mueller Co. NO USE IS TO BE MADE OF THIS DATA EXCEPT AS SPECIFICALLY AUTHORIZED BY Mueller Co. ASSENT ON THE PART OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED