



VALVE SIZE	A	B	C	D	E	F	G	H	J	K	L
2 1/2	7.50	6.19	3.50	2.50	5.50	7	0.75	4	--	--	0.69
3	8.19	3.75	3	6.00	7.50	0.75	4	--	--	--	0.75
4	9	7.25	4.50	4	7.50	9	0.75	6	0.63	2	0.94
5	10	8.38	5.75	5	8.50	10	0.88	6	0.75	2	0.94
6	10.50	8.38	5.75	6	8.50	11	0.88	6	0.75	2	1
8	11.50	10.69	7.63	8	11.75	13.50	0.88	6	0.75	2	1.13

THIS DRAWING IS THE PROPERTY OF
HENRY PRATT COMPANY
AND MUST NOT BE USED IN ANY WAY
PREJUDICIAL TO THEIR INTERESTS

ITEM	QTY	DESCRIPTION	MATERIAL
107	1	CAP SCREW	STL/ZINC
108	1	RETAINING WASHER	STL/ZINC
106	1	TORQUE ADJ. BOLT	STL/ZINC
104	1	BODY STOP	STL/ZINC
103	1	ADJ. CLOSE STOP	STL/ZINC
102	1	ADJ. OPEN STOP	STL/ZINC
101	1	TORQUE COLLAR	DUCTILE IRON
10	1	CAP SCREW	STL/ZINC
9	2	WASHER	PTFE
8	1	WASHER	BRASS
7	1	Ø RING	ELAS AS SPEC.
6	2	U CUP SEAL	ELAS AS SPEC.
5	1	RETAINING RING	SPRING STEEL
4	2	SLEEVE BEARING	316 STN. STEEL
3	1	PLUG ASSEMBLY	DUCTILE IRON
2	1	GAP	A 126 CL B
1	1	BODY	A 126 CL B

PRATT
Henry Pratt Company

DATE: _____ BY: _____ TITLE: _____

REVISIONS: _____

SCALE: 2 1/2" = 8"

PLUG VALVE FLANGED, WRENCH OPERATED

DWG. NO. HP 49010