

Mueller Co.

HYDRANT LUBRICANT

Mueller® Hydrant Lubricant was developed to meet the special needs of hydrant lubrication. It provides lasting lubrication at all temperatures and in the severe conditions under which hydrants operate. Mueller® Hydrant Lubricant helps ensure efficient, trouble-free hydrant operation.

- ✓ Intended specifically for this application
- ✓ Water-white, low-odor fluid
- ✓ Produced from high-quality base oils
- ✓ Meets 21 CFR 172.878 and 21 CFR 178.3620 (a)

Property	Method	Limit
Specific Gravity at 25°C/25°C	ASTM D4052	0.875 - 0.905
Kinematic Viscosity at 40°C, mm ² /s	ASTM D445	18.0 – 20.0
Acidity	NF (Current Revision)	Pass
Solid Paraffin	NF (Current Revision)	Pass
Limit of Polycyclic Aromatic Hydrocarbons	NF (Current Revision)	Pass
Limit of Sulfur Compounds	NF (Current Revision)	Pass
Residual Solvents, Reportable Quantity	USP 467	None
Odor	LATM 092	None
Color, Saybolt	ASTM D156	30 Min.
Pour Point, °F, (°C)	ASTM D97	-35 (-37) Max.



Mueller Part Numbers:
195166 (55 Gallon Drum)
184048 (1 Gallon)
280354 (10.5 oz.)

Mueller Co.

Albertville, AL 35950
www.muellercompany.com
Mueller Customer Service: 800-423-1323
Manufactured for Mueller Co. by Pressure-Lube, Inc.