

**PRE-1965 CHATTANOOGA
FIRE HYDRANT
REPLACEMENT PARTS**



UL / FM

FIRE PROTECTION PRODUCTS

Rev. 4-14

Shaded area
indicates
change

Catalog Part Number	Description	Material	Material Standard
H-1	Oil Screw	Bronze	ASTM B36 Alloy 268
H-2	Operating Nut	Bronze	ASTM B62
H-3	Weather Cap	Bronze	ASTM B62
H-4	Hold Down Nut	Bronze	ASTM B62
H-5	Oiler	Steel	-
H-16	Hose Nozzle Cap	Cast Iron	ASTMA126 Class B
H-17	Hose Nozzle Gasket	Rubber	ASTM D2000 3BC720
H-24	Test Plug	Brass	ASTM B16
H-26	Barrel Gasket	Rubber	ASTM D2000 2AA805
H-28	Stem Top Section	Bronze	ASTMB584 Alloy 864
H-29	Upper Stem Pen	Bronze	ASTM B21 Alloy 464
H-32	Nozzle Cap Chain	Steel	-
H-35	Stem	Steel	ASTMA576 Grade 1117
H-36	Upper Valve Plate	Bronze	ASTM B62
H-37	Drain Valve Facing Screw	Bronze	ASTM B36 Alloy 268
H-39	Seat Ring	Bronze	ASTM B62
H-40	Lower Barrel	Cast Iron	ASTMA126 Class B
H-41	Shoe Gasket	Rubber	ASTM D2000 2AA805
H-42	Shoe Bolt and Nut	Steel	ASTMA307 Grade B
H-43	Metallic Gasket	Copper-fiber	-
H-44	Main Valve	Rubber	ASTM D2000 4AA915
H-45	Lower Valve Plate	Cast Iron	ASTMA126 Class B
H-46	Valve Plate Nut	Bronze	ASTM B62
H-47	Shoe	Cast Iron	ASTMA126 Class B
H-49	Drain Valve Facing	Leather	-
H-50	Cap Nut	Bronze	ASTM B62
H-93	O-ring Seal	Rubber	ASTM D2000 3CH720

Size of Hydrant	DIMENSIONS				
	A	B	C	D	E
5-1/4"	30-7/8"	17-1/4"	7"	8-1/8"	3-3/8"

