

## FIRE PROTECTION PRODUCTS

Catalog Part Number	Description	Material	Material Standard
A-1	Operating Nut	Bronze	ASTM B584
A-2	Weather Cap <i>(not shown and used only on pre-1988 models)</i>	Cast Iron	ASTM A126 CL.B
A-3	Hold Down Nut o-ring	Rubber	ASTM D2000 BUNA N
A-4	Hold Down Nut <i>(not shown and used only on pre-1988 models)</i>	Bronze	ASTM B584
A-5	Bonnet o-ring	Rubber	ASTM D2000 BUNA N
A-6	Anti-friction Washer**	Acetal	-
A-7	Oil Plug	Brass	ASTM B16
A-8	Bonnet	Cast Iron	ASTM A126 CL.B
A-9	Bonnet Bolt and Nut****	Steel	SAE J429 Grade 2
A-10	Bonnet o-ring <i>(1997 and newer 3-way models: all pre 1997 models and 1-way and 2-way models have flat gaskets)</i>	Rubber	ASTM D2000 BUNA N
A-11	Upper Stem	Steel	ASTM A576 GR.B
A-12	Stem o-ring	Rubber	ASTM D2000 BUNA N
A-13	Nozzle Lock	Stainless Steel	ASTM A276
A-14	Pumper Nozzle	Bronze	ASTM B584
A-15	Pumper Nozzle Gasket	Rubber	ASTM D2000 Neoprene
A-16	Pumper Nozzle o-ring	Rubber	ASTM D2000 BUNA N
A-17	Pumper Nozzle Cap	Cast Iron	ASTM A126 CL.B
A-18	Hose Nozzle	Bronze	ASTM B584
A-19	Hose Nozzle Gasket	Rubber	ASTM D2000 Neoprene
A-20	Hose Nozzle o-ring	Rubber	ASTM D2000 BUNA N
A-21	Hose Nozzle Cap	Cast Iron	ASTM A126 CL.B
A-22	Cap Chain	Steel	Plated
A-23	Chain Ring	Steel	Plated
A-24	Upper Barrel Less Nozzles	Cast Iron	ASTM A126 CL.B
A-25	Safety Coupling	Stainless Steel	ASTM A890
A-26	Safety Flange Bolt and Nut****	Steel	SAE J429 Grade 2
A-27	Safety Flange o-ring <i>(1997 and newer 3-way models: all pre 1997 models and 1-way and 2-way models have flat gaskets)</i>	Rubber	ASTM D2000
A-28	Safety Flange	Cast Iron	ASTM A126 CL.B
A-29	Cotter Pin	Stainless Steel	ASTM A276
A-30	Clevis Pin	Stainless Steel	ASTM A276
A-31	Lower Stem	Steel	ASTM A576 GR.B
A-32	Lower Barrel	Cast Iron	ASTM A126 CL.B
A-33	Stem Pin	Stainless Steel	ASTM A276
A-34	Drain Valve Facing	Plastic	-
A-35	Drain Valve Screw	Stainless Steel	ASTM A276
A-36	Upper Valve Plate <i>(includes A-34 and A-35)</i>	Bronze	ASTM B584
A-37	Shoe Bolt and Nut****	Steel	SAE J429 Grade 2
A-38	Drain Ring Housing o-ring <i>(1997 and newer 3-way models: all pre-1997 models have a square gasket)</i>	Rubber	ASTM D2000 BUNA N
A-39	Seat Ring Top o-ring	Rubber	ASTM D2000 BUNA N
A-40	Drain Ring Housing	Cast Iron	ASTM A126 CL.B
A-41	Drain Ring Housing Bolt and Nut <i>(not shown: use only on pre-1997 model hydrants)</i>	Steel	ASTM A307 Plated
A-42	Drain Ring	Bronze	ASTM B584
A-43	Seat Ring	Bronze	ASTM B584
A-44	Seat Ring Bottom o-ring	Rubber	ASTM D2000 BUNA N
A-45***	Reversible Main Valve <i>(1997 and newer models only: pre-1997* models use non-reversible main valve and lower valve plate - not shown)***</i>	Rubber	ASTM D2000
A-46	Lower Valve Plate <i>(1997 and newer for reversible main valve: pre-1997 models use non-reversible main valve - not shown)</i>	Cast Iron	ASTM A126 CL.B
A-47	Cap Nut Seal	Rubber	ASTM D2000
A-48	Lock Washer	Stainless Steel	ASTM A276
A-49	Lower Valve Plate Nut	Cast Iron	ASTM A126 CL.B
A-50	Shoe	Ductile Iron	ASTM A536
A-84	Hold Down Nut	Bronze	ASTM B584
A-85	Weather Seal	Rubber	ASTM D2000

\* Pre-1997 models may be upgraded to use the reversible main valve by also replacing the lower valve plate with the 1997 model.

\*\* For 350 psig option, A-6 is a roller thrust bearing, Steel.

\*\*\* For 350 psig option, A-45 is Rubber ASTM D2000 reinforced with Cast Iron ASTM A126 CL.B

\*\*\*\* For 350 psig option, A-9, 27, and 37 are Steel SAE J429 Grade 5 Plated