

**MUELLER® LINESEAL III®, LINESEAL XP™,  
LINESEAL XP11®, LINESEAL 350™ BUTTERFLY  
VALVE ORDERING INSTRUCTIONS**



**11.21**

Shaded area indicates change Rev. 11-16

**Ordering Instructions for MUELLER® LINESEAL III®, LINESEAL XP™, LINESEAL XP11® &  
LINESEAL 350™ Butterfly Valves with Cylinder Actuators†**

1. Quantity: \_\_\_\_\_

2. Size of Valve: \_\_\_\_\_

3. Body Style:

\_\_\_\_\_ FLG x FLG (3"-48" ANSI B16.1 Class 125)

\_\_\_\_\_ FLG x FLG (3"-48" ANSI B16.1 Class 250)

\_\_\_\_\_ MJ x MJ (4"-48")

\_\_\_\_\_ FLG x MJ (6"-36")

Other: \_\_\_\_\_

*Note: MJ valves are supplied without accessory kits standard.*

4. Class of valve \_\_\_\_\_

5. Please provide the following information in addition to the valve class (if known) listed in question 4.

PRESSURE: Normal \_\_\_\_\_ psig Maximum \_\_\_\_\_ psig

FLOW: Normal \_\_\_\_\_ psig Maximum \_\_\_\_\_ psig

6. Type of service: Water \_\_\_\_\_ Air \_\_\_\_\_

7. Cylinder Supply Available:

Water \_\_\_\_\_ Air \_\_\_\_\_ Air/Oil \_\_\_\_\_ Oil \_\_\_\_\_

8. Minimum Supply Pressure Available to Actuate Cylinder: \_\_\_\_\_ psig

9. Fail Safe Spring Return Required?

Yes \_\_\_\_\_ No \_\_\_\_\_

10. Manual Override Required?

Yes \_\_\_\_\_ No \_\_\_\_\_

11. Accessories: Speed Control \_\_\_\_\_ Positioner

\_\_\_\_\_ Solenoid \_\_\_\_\_ Limit Switches (qty) \_\_\_\_\_

Other \_\_\_\_\_

12. Cylinder Material:

Non-Metallic \_\_\_\_\_ Metallic \_\_\_\_\_

13. Valve Function: Open/Close \_\_\_\_\_ Modulating \_\_\_\_\_

14. Maximum Fluid Line Temperature \_\_\_\_\_ °F.

15. Coating Requirement\*:

\_\_\_\_\_ mils of Ameron 370 (4 or 8 standard)

16. Number of Certificates of Compliance to AWWA C-504 required. \_\_\_\_\_

Please note below any additional information or requirements such as extended bonnets and torque tubes, floor stand mounted actuators, special actuator positioning, and special coatings.

PLEASE PROVIDE AS MUCH DESCRIPTIVE INFORMATION AND/OR SPECIFICATIONS AS POSSIBLE TO ENABLE US TO PROVIDE THE MOST SUITABLE VALVE FOR YOUR NEEDS. DO NOT HESITATE TO ATTACH ADDITIONAL PAGES.

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Accessory items required (Stems Guides, Ground Line Position Indicators, Floor Stands, etc.).\*\*

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

\*In order to provide valves that meet NSF 61 requirements and certify to that, Ameron 370 will be the paint supplied between 4-24mils thickness. Other paints or mil thickness greater 24 mils will not be NSF 61 compliant.

\*\*Accessory items are listed on pages 11.3, 11.10, and 11.12.

†Please provide Cylinder Specifications if available.