

# U.S. PIPE T-28 DUCTILE IRON TAPPING SLEEVE



# 12.5

Shaded area indicates change Rev. 7-16

- Catalog number--**T-28** Dual Compression Seal Tapping Sleeve
- Sizes--range from 6"-16" main and outlet (see chart below for available size)
- Fits all classes of pipe through Class D pit cast gray iron
- 3/8" test plug standard
- Epoxy coated ductile iron construction
- O-ring seals on outlet and flange connection
- Outlet flange dimensions and drilling comply with ANSI ASME/ANSI B16.1 Class 125 and with MSS SP-60
- 304 Stainless steel bolts
- 250 psig (1725 kPa/17 barg) maximum working pressure



**T-28**

## Tapping Sleeve pipe information

Nominal size of main	O.D. Range of sleeve		Class and type of pipe
	in.	mm	
6"	6.90 - 7.10	175.26 - 180.34	Fits all classes of pipe through Class D pit cast gray iron.
8"	9.05 - 9.30	229.87 - 236.22	
10"	11.10 - 11.40	281.94 - 289.56	
12"	13.20 - 13.50	335.28 - 342.90	
16"	17.40 - 17.80	441.96 - 452.12	

## Sizes available

Nominal size of main	Outlet size				
	4"	6"	8"	10"	12"
6"	X	X	-	-	-
8"	X	X	X	-	-
10"	X	X	X	X	-
12"	X	X	X	X	X
16"	X	X	X	X	X