

Typical Xtra-Range
Servi-Seal Clamp



Style number 551-559

Mueller 551 - 559 Xtra-Range Servi-Seal All Stainless Steel Pipe Repair Clamps - with 3/4" through 2" IP/CC Threaded service outlet - for 3" through 12" cast iron, ductile iron steel, A-C and PVC pipe

To specify the catalog number, provide the following information :

1. Style number—551-559 (see chart below)
2. Length—Standard length available (inches): 7-1/2, 10, 12-1/2, 15, 20, 30
3. Size number—from chart on page 15.22
4. Catalog number prefix for optional features, if desired.

The catalog number for a Xtra-Range Servi-Seal Repair Clamp, with a 3/4" IP outlet, 12" clamp length for 6" cast iron pipe is 551-12-684

Clamp style number	Clamp length	Clamp size number
551	12	684

Clamp style number

Style number	Size/type of outlet tapping thread	Sizes available*
551	3/4" IP	3.49-14.80
552	3/4" CC	3.49-14.80
553	1" IP	3.49-14.80
554	1" CC	3.49-14.80
555	1-1/4" IP	4.74-14.80
556	1-1/2" CC	4.74-14.80
557	1-1/2" IP	4.74-14.80
558	2"CC	4.74-14.80
559	2"IP	4.74-14.80


*Clamps available to fit specific size pipe within this nominal range.



550 Series nut & washer

Extra Nuts and Washers for Mueller Single Section Full Seal All Stainless Repair Clamps

Clamp size	Nut part number	Washer part number
3"-12" (standard nut)	311581	311582




Bonding device

Deep socket wrenches

Specially designed for use with Mueller Full-Seal Repair Clamps. Long ratchet handle has thumb-tip reverse. Deep sockets (3-1/4") have double hex (12 pt.) and 1/2" square drive.



Part number	Description
515204	15-3/4" with reversible ratchet handle
515207	1-1/16" socket for 4" and larger clamps



Bonding device

Bonding device for cathodic protection

Metallic conductors are set in the gasket to provide contact between the band and the pipe surface and are available on all 500 series clamps. These conductors permit electrical current flow by establishing positive contact with pipe and band on each side of the pipe crack or break.

To specify optional bonding device for cathodic protection, add a prefix of "2" to catalog number. Example: 2-551-12-684.

Note: For O.D. not shown contact our Customer Service Center or your Mueller Sales Representative.

IMPORTANT: MUELLER PIPE REPAIR CLAMPS have demonstrated their capability to seal against water pressures commonly encountered in distribution systems. Smaller diameter clamps of a given design can seal against higher pressures than larger ones. In addition, the pressure that a clamp can contain depends upon the torque applied to the bolts, the uniformity of bolt tightening (when there is more than one bolt), as well as the type and extent of pipe damage, surface condition of the pipe, environmental conditions, and installation workmanship.

▲ WARNING: Use on A-C pipe, which contains a known carcinogen, requires appropriate protective equipment and procedures be employed.