Mueller Co.
Reliable Connections™

MUELLER® XTRA-RANGE® SERVI-SEAL® ALL STAINLESS STEEL PIPE REPAIR CLAMPS

Rev. 9-09 Shaded area indicates changes

Mueller 551-559 Series Xtra-Range Servi-Seal All Stainless Steel Pipe Repair Clamps — for 3" through 12" cast iron, ductile iron , A-C and PVC plastic pipe. Standard Lengths: 7-1/2", 10", 12-1/2", 15", 20", 30"

Nominal Pipe Size	Clamp size - number	Clamp O.D. range*				Cast Iron	Ductile Iron	Cast Iron O.D. PVC	Steel***	A-C Rough Barrel
		Inches		Millimeters						
		Min.	Max	Min.	Max					
3"	349	3.49	4.29	88.6	109.0	-	-	-	-	-
4"	444	4.44	5.24	112.8	133.1	-	-	-	-	-
4"	474	4.74	5.57	120.4	141.5	50-250, A, B, C, D	All	Class 150, 200	-	Class 100**, 150, 200
6"	662	6.62	7.42	168.1	188.5	-	-	-	STD	-
6"	684	6.84	7.64	173.7	194.7	50-250, A, B, C, D	All	Class 150, 200	-	Class 100**, 150, 200
8"	862	8.62	9.42	218.9	293.3	-	-	-	STD	-
8"	899	8.99	9.79	228.3	248.7	50-250, A, B, C, D	All	Class 150, 200	-	Class 100**, 150, 200
10"	1075	10.75	11.55	273.0	293.4	-	-	-	-	-
10"	1110	11.10	11.90	281.9	302.3	50-250, A, B, C, D	All	Class 150, 200	-	Class 100**
10"	1160	11.60	12.40	294.6	315.0	-	-	-	-	Class 150, 200
12"	1275	12.75	13.55	323.8	344.2	-	-	-	-	-
12"	1320	13.20	14.00	335.3	355.6	50-250, A, B, C, D	All	Class 150, 200	-	Class 100**
12"	1365	13.65	14.45	346.7	367.0	-	-	-	-	Class 100**, 150, 200
12"	1400	14.00	14.80	355.6	375.9	-	-	-	-	-

**Verify pipe O.D. before selecting clamp size.*
***CAUTION—O.D. of class 100 A-C pipe varies greatly. Measure pipe O.D. to assure proper clamp selection.*

Note: For O.D. not shown contact our Customer Service Center or your Mueller Sales Representative.

⚠ *WARNING: Use on A-C pipe, which contains a known carcinogen, requires appropriate protective equipment and procedures be employed.*