

MUELLER® H-13000 & S-13000 SERIES BRONZE SERVICE SADDLES FOR IPS PVC PIPE

Rev. 5-11 Shaded area indicates change

MUELLER® Service Saddles for iron pipe size PVC pipe

- Outlet tapped with either AWWA taper (C.C.) or AWWA I.P. (F.I.P.T.) thread
- For use on IPS PVC pipe (O.D. controlled)
- 3/4" - 2" tap sizes
- NSF 61 Certified
- 200 psi (1380 kPa/13 barg) maximum working pressure



S-13000 Series
2-piece hinged
2" to 8" mains;
3/4" to 1" tapping



H-13000 Series
2-piece
2" to 8" mains;
3/4" to 1" tapping



H-13000 Series
2-piece
4"-8" mains;
1-1/2" or 2"
tapping



H-13000 Series
3-piece
10" & 12" mains;
3/4" to 1"
tapping

MUELLER® Service Saddles for IPS PVC pipe

Nominal Main Size	Type Of Thread In Service Saddle Outlet										Design	
	AWWA Taper Thread (C.C.)					Design	AWWA Iron Pipe Thread (F.I.P.T)					Design
	Catalog Number	Tapping Size					Catalog Number	Tapping Size				
	3/4"	1"	1-1/2"	2"		3/4"	1"	1-1/2"	2"			
2"	S-13420	X	X	-	-	Two piece	S-13470	X	X	-	-	Two piece
2"	H-13420	X	X	-	-		H-13470	X	X	-	-	
2-1/2"	S-13422	X	X	-	-		S-13472	X	X	-	-	
2-1/2"	H-13422	X	X	-	-		H-13472	X	X	-	-	
3"	S-13425	X	X	-	-		S-13475	X	X	-	-	
3"	H-13425	X	X	-	-		H-13475	X	X	-	-	
4"	S-13428	X	X	-	-		S-13478	X	X	-	-	
4"	H-13428	X	X	X	X		H-13478	X	X	X	X	
6"	S-13431	X	X	-	-		S-13481	X	X	-	-	
6"	H-13431	X	X	X	X		H-13481	X	X	X	X	
8"	S-13433	X	X	-	-	S-13483	X	X	-	-		
8"	H-13433	X	X	X	X	H-13483	X	X	X	X		
10"	H-13434	X	X	-	-	H-13484	X	X	-	-	Three piece	
12"	H-13435	X	X	-	-	H-13485	X	X	-	-	Three piece	

These machines may be used with the service saddles illustrated on this page

Machine	Service Saddle Tap Size			
	3/4"	1"	1-1/2"	2"
E-5™	X	X	X	X
D-5™	X	X	X	X
TRU-CUT™	X	X	-	-
MEGA-CUT™	X	X	X	X
PL-2™	X	X	-	-