

# SERVICE FITTINGS WITH I.P. THREADED COPPER FLARE CONNECTION


Shaded area indicates change Rev. 4-14



**Straight three part union**  
I.P. threaded copper flare nut  
-both ends

**H-15402N**

|      |
|------|
| 3/4" |
|------|



**Straight coupling**  
I.P. threaded copper flare nut  
x F.I.P. thread

**H-15452N**


|        |      |
|--------|------|
| 3/4" ‡ | 1" ‡ |
|--------|------|



**Straight coupling**  
I.P. threaded copper flare nut  
x M.I.P. thread

**H-15427N**

|      |
|------|
| 3/4" |
|------|



**Straight coupling**  
I.P. threaded copper flare nut  
x female increasing I.P. thread  
(this thread is one size larger  
than nominal size of fitting)

**H-15467N**

|      |
|------|
| 3/4" |
|------|



**Copper flare nut I.P. threaded**

**H-15432N**

|      |    |
|------|----|
| 3/4" | 1" |
|------|----|

FOR OTHER FLARE CONNECTION OPTIONAL EQUIPMENT, SEE PAGE 6.7

‡ Requires minimum ordering quantity. Contact MUELLER Customer Service Center for minimum ordering requirements and availability.  
NOTE: Sizes shown above represent nominal size of fitting.