



Two branch
 *Inlets: Copper flare nut
 *Outlet: F.I.P. thread

H-15342N

1"x2"



Two branch-short body
 *Inlets: M.I.P. thread
 *Outlet: M.I.P. thread

H-10070N

3/4"x1"



Two branch - Short body
 *Inlets: Solder joint
 *Outlet: MUELLER 110[®]
 Conductive Compression
 Connection for CTS
 O.D.** tubing

H-15344N

1"x1-1/2"

1"x2"



Two branch
 *Inlets: MUELLER INSTA-TITE
 Connection for IPS* PE pipe
 *Outlet: MUELLER INSTA-TITE
 Connection for IPS* PE pipe

H-15353N

3/4"x1"



Two branch
 *Inlets: MUELLER 110[®]
 Conductive Compression
 Connection for IPS PE pipe
 *Outlet: MUELLER 110[®]
 Conductive Compression
 Connection for IPS PE pipe

H-15354N

3/4"x1"

NOTE: Minimum length of copper tubing "gooseneck" is: 3/4" size-30", 1" size-40".

‡Requires minimum ordering quantity. Contact MUELLER Customer Service Center for minimum ordering requirements and availability.

*Inlets and outlet can be reversed.

**See page 6.29 for tubing that can be used with this connection.