


SERVICE FITTINGS WITH COPPER FLARE CONNECTION


Shaded area indicates change Rev. 3-16



Straight union
Extra strong (XS) lead flange
coupling x copper flare nut

H-15506N


1/2"	1/2" x 3/4"	5/8" x 3/4"	3/4"	3/4" x 5/8"
------	-------------	-------------	------	-------------



Eighth bend coupling
Swivel nut with female extra
strong (XS) lead flange thread
x copper flare nut

H-15516N

5/8" x 3/4"	3/4"	1"
-------------	------	----



Straight coupling
Female extra strong (XS)
lead flange thread x copper
flare nut

H-15505N

1/2"	1/2" x 3/4"	5/8"	5/8" x 3/4"	3/4"
3/4" x 1"	1"	1" x 3/4"	1-1/4" x 1"	1-1/2" 2"



Straight coupling
Female double extra strong
(XXS) lead flange thread x
copper flare nut

H-15510N

5/8" x 3/4"	3/4"	2"
-------------	------	----



Eighth bend coupling
Female extra strong (XS) lead
flange thread x copper flare nut

H-15515N

5/8" x 3/4"	3/4"	1"
-------------	------	----



Quarter bend coupling
Female extra strong (XS)
lead flange thread x copper
flare nut

H-15513N


1/2" x 3/4"	5/8" x 3/4"	3/4"	1" ‡	1" x 3/4"
-------------	-------------	------	------	-----------



Quarter bend coupling
Female extra strong (XS)
lead flange thread x copper
flare nut (pre-1920)

H-15513-03N

1" x 3/4"



Eighth bend coupling
Female double extra strong
(XXS) lead flange thread x
copper flare nut

H-15521N

1/2" x 3/4"	3/4"
-------------	------

NOTE: Sizes shown above represent nominal size of fitting. When two sizes are given, first is size of lead flange end and second is size of copper flare nut.
‡Requires minimum ordering quantity. Contact MUELLER Customer Service Center for minimum ordering requirements and availability.

MUELLER Service Tees are manufactured and tested in accordance with ANSI/AWWA C800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.