

CAST IRON METER BOXES FOR 5/8"x3/4" METERS

With locking lid, angle inlet and 3/4" FIP horizontal coupling outlet

Inlet coupling	Inlet size	Box height	Catalog number
Mueller 110 (CTS)	3/4"	7"	H-1452-AN
Mueller 110 (CTS)	3/4"	9"	H-1452-AN
INSTA-TITE (CTS)	3/4"	7"	H-1452-BN
INSTA-TITE (CTS)	3/4"	9"	H-1452-BN
Mueller 110 (IPS)	3/4"	7"	H-1452-CN
Mueller 110 (IPS)	3/4"	9"	H-1452-CN
INSTA-TITE (IPS)	3/4"	7"	H-1452-DN
INSTA-TITE (IPS)	3/4"	9"	H-1452-DN
Copper flare	3/4"	7"	H-1452-EN
Copper flare	3/4"	9"	H-1452-EN
Mueller 110 (CTS)	1"	7"	H-1452-JN
Mueller 110 (CTS)	1"	9"	H-1452-JN
Copper flare*	3/4"	7"	H-1452-2N
Copper flare*	3/4"	9"	H-1452-2N
Mueller 110 (CTS)*	3/4"	7"	H-1452-3N
Mueller 110 (CTS)*	3/4"	9"	H-1452-3N
Pack Joint (CTS)	3/4"	7"	H-1452-AN
Pack Joint (CTS)	3/4"	9"	H-1452-AN
Pack Joint (CTS)	1"	7"	H-1452-JN
Pack Joint (CTS)	1"	9"	H-1452-JN
Pack Joint (CTS)*	3/4"	7"	H-1452-3N
Pack Joint (CTS)*	3/4"	9"	H-1452-3N



(H-1452-3N shown)

* Inlet connections are integral to the meter box.

Note: Meter boxes will not be sold without the inlet coupling.

Touch read hole available. Contact Mueller Customer Service Center for more information.

Note: For an inlet reduced port ball valve replace the "H1" with a "B2" when ordering. Example: H1452-3N - B2452-3N

With non-locking lid, angle inlet and 3/4" FIP horizontal coupling outlet

Inlet coupling	Inlet size	Box height	Catalog number
Mueller 110 (CTS)	3/4"	7"	H-1453-AN
Mueller 110 (CTS)	3/4"	9"	H-1453-AN
INSTA-TITE (CTS)	3/4"	7"	H-1453-BN
INSTA-TITE (CTS)	3/4"	9"	H-1453-BN
Mueller 110 (IPS)	3/4"	7"	H-1453-CN
Mueller 110 (IPS)	3/4"	9"	H-1453-CN
INSTA-TITE (IPS)	3/4"	7"	H-1453-DN
INSTA-TITE (IPS)	3/4"	9"	H-1453-DN
Copper flare	3/4"	7"	H-1453-EN
Copper flare	3/4"	9"	H-1453-EN
Copper flare*	3/4"	7"	H-1453-2N
Copper flare*	3/4"	9"	H-1453-2N
Mueller 110 (CTS)*	3/4"	7"	H-1453-3N
Mueller 110 (CTS)*	3/4"	9"	H-1453-3N
Pack Joint (CTS)	3/4"	7"	P-1453-AN
Pack Joint (CTS)	3/4"	9"	P-1453-AN
Pack Joint (CTS)*	3/4"	7"	P-1453-3N
Pack Joint (CTS)*	3/4"	9"	P-1453-3N



(P-1453-3N shown)

* Inlet connections are integral to the meter box.

Note: Meter boxes will not be sold without the inlet coupling.

Touch read hole available. Contact Mueller Customer Service Center for more information

Note: For an inlet reduced port ball valve replace the "P1" with a "P2" when ordering. Example: P1453-3N - P2453-3N

See pages 8C.5, 8C.6 and 8C.7 for tubing or pipe that can be used with MUELLER 110®, Pack Joint and INSTA-TITE® connections.

MUELLER Valves and Couplings are manufactured and tested in accordance with ANSI/AWWA C800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.