GROUND KEY ANGLE METER VALVES & SERVICE VALVES - 3/4"-2"

Rev. 4-14 Shaded area indicates change

Ground Key Angle Meter Valve
MUELLER 110® Conductive Compression Connection for CTS
O.D.* tubing x meter flange
180° turn check - lock wing

H-14277N

Catalog size	1-1/2"	2" † †
Meter size	1-1/2"	1-1/2", 2"
Tubing size	1-1/2"	2"

Ground Key Angle Meter Valve
MUELLER® Pack Joint Connection for CTS O.D.* tubing x meter flange
180° turn check - lock wing

P-14277N

Catalog size	1-1/2"	2" † †
Meter size	1-1/2"	1-1/2", 2"
Tubing size	1-1/2"	2"

Ground Key Angle Meter Valve
Copper flare nut x meter flange
180° turn check - lock wing

H-14276N

Catalog size	1-1/2"	2" † †
Meter size	1-1/2"	1-1/2", 2"
Tubing size	1-1/2"	2"

Ground Key Angle Meter Valve
F.I.P. x meter flange
180° turn check - lock wing

H-14286N

Catalog size	1-1/2"	2" † †
Meter size	1-1/2"	1-1/2", 2"
Tubing size	1-1/2"	2"

Ground Key Angle Meter Valve
F.I.P. x F.I.P.
180° turn check - lock wing

H-14285N

Catalog size	3/4

MUELLER Solid Tee Head Roundway Meter Stop
F.I.P. x F.I.P.
360° turn - lock wing

H-10281N

Catalog size	1-1/2"

** See charts on pages 8D.17 and 8D.18 for tubing that may be used with these connections.*
††These valves have meter flanges double drilled to fit either 1-1/2" or 2" meters.

MUELLER Valves and Couplings are manufactured and tested in accordance with ANSI/AWWA C800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.