



Straight dual check valve
Inlet: M.I.P.
Outlet: F.I.P.
 To order ASSE approved†† model add suffix -A to catalog number

H-14241N

Catalog size	3/4"	3/4"x1" ††	1"
Pipe size	3/4"	3/4" in, 1" out	1"



Straight dual check valve
Inlet: F.I.P.
Outlet: F.I.P.
 To order ASSE approved†† model add suffix -A to catalog number

H-14243N

Catalog size	3/4"	3/4"x1" ††	1"	1-1/2" ††	2" ††
Pipe size	3/4"	3/4" in, 1" out	1"	1-1/2"	2"



Straight dual check valve
Inlet: Meter swivel nut*
Outlet: F.I.P.
 To order ASSE approved model add suffix -A to catalog number

H-14242N

Catalog size	5/8"x3/4"x3/4"	5/8"x3/4"x1" ††	1"	1-1/2" ††, †††	2" †, ††
Pipe size	5/8"x3/4", 3/4"	5/8"x3/4", 3/4"	1"	1-1/2"	1-1/2", 2"
Tubing size	3/4"	1"	1"	1-1/2"	2"



Straight dual check valve
Inlet: M.I.P.
Outlet: MUELLER 110 Conductive Compression Connection for CTS O.S. ** tubing.
 To order ASSE approved†† model add suffix -A to catalog number

H-14283N


Catalog size	3/4
Pipe size	3/4



Straight dual check valve
Inlet: M.I.P.
Outlet: M.I.P.
 To order ASSE approved†† model add suffix -A to catalog number

H-14282N

Catalog size	3/4
Pipe size	3/4



Straight dual check valve
Inlet: Meter swivel nut*
Outlet: M.I.P.
 To order ASSE approved†† model add suffix -A to catalog number

H-14272N

Catalog size	5/8"x3/4"x3/4"
Meter size	5/8"x3/4", 3/4"
Tubing size	3/4"

8D-VALVES/CHECKS

* Meter swivel nuts are regularly furnished with a saddle feature to aid in meter installation and removal. A plain swivel nut is available as an option by adding a suffix of -1 to the catalog number.
 ** See charts on page 8D.17 and 8D.18 for tubing and pipe that can be used with this connection.
 †These valves have meter flanges double drilled to fit either 1-1/2" or 2" meters.
 ††These 3/4"x1", 1-1/2" and 2" sizes are not available as ASSE approved.
 †††These have meter flanges for 1-1/2" meters