

# 8F.4



# MUELLER® ADJUSTA-COIL® METER BOX

Rev. 4-14 Shaded area indicates change

## MUELLER ADJUSTA-COIL Meter Box ordering instructions

To order a MUELLER ADJUSTA - COIL Meter Box, simply choose the options you require from the nine categories listed below and place the option code on the

appropriate line of the catalog number shown below. If the box you need is a tandem type, please fill out the tandem information box shown below the options listing and contact the factory for price and delivery information. Phone 1-800-423-1323 or fax 1-217-425-7537.

### Catalog Number

(1) \_\_\_\_\_ (2) \_\_\_\_\_ (3) \_\_\_\_\_ (4) \_\_\_\_\_ (5) \_\_\_\_\_ (6) \_\_\_\_\_ (7) \_\_\_\_\_ (8) \_\_\_\_\_ (9) \_\_\_\_\_

### Options

**1** Meter size  
NOTE: Meter is **not** furnished. Order meter separately.

Meter Size	Code Number
5/8"	200
5/8" x 3/4"	203
3/4"	250
1"	330

**2** Box Style

Box Style	Code Number
Single meter	AS
Double meter	AD
Tandem	AT

**3** Box diameter

Box Diameter	Code Number
<b>15" box is for use with:</b> 5/8, 5/8 x 3/4 or 3/4 single meters 5/8, 5/8 x 3/4 or 3/4 tandems*	15
<b>18" box is for use with:</b> 1" single meters 1" tandems 5/8, 5/8 x 3/4 or 3/4 double meters	18

**4** Adjusta-coil depth

Depth Range*	Code Number	Adjustment Range
36" Min to 42" Max	3642	6" (Below 48")
42" Min to 48" Max	4248	
48" Min to 60" Max	4860	12" (48" & Above)
54" Min to 66" Max	5466	
60" Min to 72" Max	6072	
66" Min to 78" Max	6678	
72" Min to 84" Max	7284	
78" Min to 90" Max	7890	
84" Min to 96" Max	8496	
90" Min to 102" Max	90102	
96" Min to 108" Max	96108	
102" Min to 114" Max	102114	
108" Min to 120" Max	108120	

\*other depth ranges available

**5** Meter inlet type

Meter Inlet	Code Number
Meter coupling	A
Lockwing angle meter stop	L
Lockwing angle ball valve (full port)	F
Lockwing angle ball valve (reduced port)	R

**6** Meter outlet type

Meter Outlet	Code Number
Meter coupling	A
Dual check valve	B
A.S.S.E. Dual check valve	S
A.S.S.E. Top entry vertical check	V
Lockwing angle meter stop	L
Lockwing angle ball valve (full port)	F
Lockwing angle ball valve (reduced port)	R

**7** Box bottom type

Bottom Type	Code Number
Attached aluminum bottom	A
Less bottom	B

**8** Type of box locking device (box is ordered with device to accept either a non-locking lid, center locking or side locking lid). Lids must be ordered separately.

Lock Type	Code Number
Non-locking	N
Center locking	L
Side locking	S

**9** Low lead brass

Code Number
N

### Tandem box ordering information

Type of tandem device (regulator, backflow preventer etc) \_\_\_\_\_  
 Size \_\_\_\_\_, lay length \_\_\_\_\_ and end connections (M, IP, FIP, etc.) \_\_\_\_\_ of the tandem device  
 Tandem device manufacturer's name \_\_\_\_\_ Tandem device model number \_\_\_\_\_

\* NOTE: Tandem device is not included and must be purchased separately. ALSO, 3/4" tandems systems when used with certain regulators may need to be placed within a 18" box; list the regulator model when specifying this system. If an ASSE check valve or ball valve is being used in a 3/4" setting then an 18" meter box will be required.

MUELLER Valves and Couplings used in these meter box assemblies are manufactured and tested in accordance with ANSI/AWWA C800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.