

Rev. 8-14 Shaded area indicates change

## MUELLER THERMAL-COIL Meter Box ordering instructions

To order a MUELLER THERMAL-COIL Meter Box, simply choose the options you require from the nine categories listed below and place the option code on the appropriate

line of the catalog number shown below.

If the box you need is a tandem type, please fill out the tandem information box shown below the options listing and contact the factory for price and delivery information. Phone 1-800-423-1323 or fax 1-217-425-7537.

### Catalog Number

(1) \_\_\_\_\_ (2) \_\_\_\_\_ (3) \_\_\_\_\_ (4) \_\_\_\_\_ (5) \_\_\_\_\_ (6) \_\_\_\_\_ (7) \_\_\_\_\_ (8) \_\_\_\_\_ (9) \_\_\_\_\_

### Options

**1** Meter size  
NOTE: Meter is **not** furnished. Order meter separately.

Meter Size	Code Number
5/8"	200
5/8" x 3/4"	203
3/4"	250
1"	330

**5** Meter inlet type

Meter Inlet	Code Number
Meter coupling	A
Lockwing angle meter stop	L
Lockwing angle ball valve (full port)	F
Lockwing angle ball valve (reduced port)	R

**2** Box Style

Box Style	Code Number
Single meter	CS
Double meter	CD
Tandem	CT

**6** Meter outlet type

Meter Outlet	Code Number
Meter coupling	A
Dual check valve	B
A.S.S.E. Dual check valve	S
A.S.S.E. Top entry vertical check	V
Lockwing angle meter stop	L
Lockwing angle ball valve (full port)	F
Lockwing angle ball valve (reduced port)	R

**3** Box diameter

Box Diameter	Code Number
<b>15" box is for use with:</b> 5/8, 5/8 x 3/4 or 3/4 single meters; 5/8, 5/8 x 3/4 or 3/4 tandems*	15
<b>18" box is for use with:</b> 1" single meters; 1" tandems; 5/8, 5/8 x 3/4 or 3/4 double meters	18

**7** Box bottom type

Bottom Type	Code Number
Attached aluminum bottom	A
Less bottom	B

**4** Box depth

Depth	Code Number	Depth	Code Number
30"	30	66"	66
36"	36	72"	72
42"	42	78"	78
48"	48	84"	84
54"	54	90"	90
60"	60	96"	96

**8** Type of box locking device (box is ordered with device to accept either a non-locking lid, center locking or side locking lid). Lids must be ordered separately.

Lock Type	Code Number
Non-locking	N
Center locking	L
Side locking	S

**9** No lead brass

Code Number
N

### Tandem box order information

Type of tandem device (regulator, backflow preventer, etc.) \_\_\_\_\_  
 Size \_\_\_\_\_, lay length \_\_\_\_\_ and end connections (M.I.P., F.I.P., etc.) \_\_\_\_\_ of the tandem device  
 Tandem device manufacturer's name \_\_\_\_\_ Tandem device model number \_\_\_\_\_

\* NOTE: Tandem device is not included and must be purchased separately. ALSO, 3/4" tandems systems when used with certain regulators may need to be placed within a 18" box; list the regulator model when specifying this system. If an ASSE check valve or ball valve is being used in a 3/4" setting then an 18" meter box will be required.