

Rev. 6-15 Shaded area indicates changes

- **Super Centurion 250™ catalog numbers**
 - UL 246, FM 1510 ANSI/AWWA C502 250 psi rated
 - A421 4-1/2" main valve opening 3-way (2 hose nozzle / 1 pumper nozzle)
 - A423 5-1/4" main valve opening 3-way (2 hose nozzle / 1 pumper nozzle)
 - A454 5-1/4" main valve opening 3-way (3 hose nozzle) *
 - A455 5-1/4" main valve opening 4-way (4 hose nozzle) *
 - A458 5-1/4" main valve opening 4-way (3 hose nozzle / 1 pumper nozzle) *
 - A459 5-1/4" main valve opening 4-way (2 hose nozzle / 2 pumper nozzle)**
 - * Hose Gate Valves required on FM Approved Models
 - ** A459 is UL Listed and ANSI/AWWA C502
- **Super Centurion 350™ catalog number**
 - UL 246, FM 1510 ANSI/AWWA C502 350 psi rated
 - A423 5-1/4" main valve opening 3-way (2 hose nozzle / 1 pumper nozzle)
 - A421 4-1/2" main valve opening 3-way (2 hose nozzle / 1 pumper nozzle)
- **Super Centurion 200™ catalog numbers**
 - UL 246, FM 1510 ANSI/AWWA C502 200 psi rated
 - A-433 4-1/2" main valve opening 2-way (2 hose nozzle)
 - A-435 5-1/4" main valve opening 2-way (2 hose nozzle)
- ANSI/AWWA C502 200 psi rated
 - A-420 4-1/2" main valve opening 2-way (2 hose nozzle)
 - A-424 4-1/2" main valve opening 1-way (1 pumper nozzle)
 - A-422 5-1/4" main valve opening 2-way (2 hose nozzle)
 - A-425 5-1/4" main valve opening 2-way (2 pumper nozzle)
 - A-423 5-1/4" main valve opening 3-way (1 hose nozzle / 2 pumper nozzle)
- 10 year limited warranty on material and workmanship
- Meets all applicable parts of ANSI/AWWA C502 Standard
- Post type dry barrel design
- Dry top design with O-ring sealed oil reservoir
- Traffic feature with stainless steel safety stem coupling
- Compression-type main valve closes with pressure for positive seal; it is made of rubber and is conveniently reversible providing a spare for long service life
- Operating nut available in wide variety of shapes and sizes-open left or right
- Field replaceable hose and pumper nozzles
- Hose and pumper nozzles have large radius, full flow openings for low friction loss
- Contoured shoe is designed for full flow
- Dual bronze drain valves provide effective barrel drainage
- 350 psig (2400 kPa/24 barg) maximum working pressure, 700 psig (4800 kPa/48 barg) static test pressure;
250 psig (1725 kPa/17 barg) maximum working pressure, 500 psig (3450 kPa/35 barg) static test pressure;
200 psig (1400 kPa/14 barg) maximum working pressure, 400 psig (2800 kPa/28 barg) static test pressure



Dimensions

