



No.	DESCRIPTION	MATERIAL
1	STEM	LOW LEAD BRASS ALLOY
2	O-RING	EPDM D2000
3	BALL	LOW LEAD BRASS ALLOY
4	GASKET - SEAL	NITRILE D2000
5	BODY	CAST LOW LEAD BRASS ALLOY
6	END PIECE	CAST LOW LEAD BRASS ALLOY
7	CAP	CAST BRASS ASTM B62 ALLOY C83600
8	SOLID PIN	AISI 303 STAINLESS STEEL
9	PJ CTS GSKT	BUNA N ASTM D2000
10	PJ WASHER	POLYPROPYLENE
11	CLPG NUT SUB	CAST BRASS ASTM B62 ALLOY C83600

SIZE	ϕA	B	C	D	E
3/4"	.750	1.485	1.719	2.352	4.071
1"	1.000	1.455	2.125	2.617	4.742

ALL WETTED PARTS ARE LOW LEAD BRASS ALLOY

FILEPATH: PRD-ENG\MUELLER\ASYSUBMITTALS\P24274N

DRFTR	RWB	3/28/14						
CHKR								
ENGR								
MGR								
			UNLESS OTHERWISE NOTED	THIRD ANGLE PROJECTION				
			SURFACE PREPARATION:					
			BREAK CORNER(S) ---- .000					
			SURFACE FINISH -- XX RMS	REF. No.				
			TOLERANCE(S):	SCALE				
			LINEAR ----- ± .000	NONE				
			ANGULAR ----- ± 0°00'					
			STK No:					
			MAT'L:					
			DESCR.					
REV	ECR	DESCRIPTION	DATE	BY	CHKR	ANGLE METER LLB BALL VALVE (PJ "CTS" x FIP)		DWG NUMBER
PER EST NO: DXXXX EST FIN WT = 0.0000 lbs						P24274N		

DWG NUMBER
P24274N
442-MRKTNG