

## MUELLER® A-3™ DRILLING AND TAPPING MACHINE EQUIPMENT FOR SPECIAL USES



### Power clevis

CATALOG NUMBER: H-10800—The power clevis is used when making taps in mains having pressure over 90 psig (620 kPa). By its use, the boring bar can be forced down and a connection made against pressures as high as 200 psig (1379 kPa). The power clevis also permits controlled withdrawal of the boring bar to prevent damage to the tool threads and shock to machine.




### By-pass clean out tap

PART NUMBER: 500529—Used to retap, clean out and remove chips or foreign matter in the threaded portion of the A-3 machine by-pass.



### Corporation stop wrench

CATALOG NUMBER: H-10048—Used to operate 3/4" and 1" corporation stops.



### Web belt

PART NUMBER: 88693—for pipe O.D. up to 12"

PART NUMBER: 89119—for pipe O.D. up to 16"

PART NUMBER: 580874—for pipe O.D. up to 36"

Replaces round or flat link chains to protect wrapped, coated, or plastic pipes.



### Flat link extension chain with bolts and nuts

PART NUMBER: 82314—2'-4" (.7m) extension chain increases 16" (406mm) chain to fit 16"-24" pipe.

PART NUMBER: 81028—5'-4" (1.6m) extension chain increases 16" (406mm) chain to fit 16"-36" pipe.

PART NUMBER: 81029—8'-2" (2.5m) extension chain increases 16" (406mm) chain to fit 16"-48" pipe.



### Chain spreader

PART NUMBER: 40321

Used when tapping pipe smaller than 6".