

Rev. 9-09

**MUELLER MEGA-CUT Drilling Machine - for drilling operations under pressure - 7/16" to 1-7/8" inclusive**

- Catalog number MEGA-CUT (Part number 39432)
- Hand operation
- Drive nut accepts a standard 7/8" socket wrench
- Designed for use on pressurized or dry mains
- Used to drill through 1/2" to 2" corporation stops and service saddles
- 12-1/8" (308 mm) boring bar travel
- Two retaining arms on feed sleeve safely retain the boring bar and help prevent line pressure from pushing the boring bar up once the cut is complete
- Use on cast iron O.D. PVC pipe, as well as cast iron or ductile iron pipe • cement lined cast iron or ductile iron pipe • A-C pipe • steel pipe • concrete pipe
- 200 psig (1380 kPa) maximum working pressure
- 150F (66C) maximum temperature rating

NOTE: The working pressure or temperature rating is reduced accordingly if any attachment, valve, or fitting subjected to pressure or temperature during the drilling operation has a maximum working pressure or temperature rating less than that specified above.



	<b>Mega-Cut</b>
Total shipping weight	29 lbs. (13 kg)
Machine only weight	19 lbs.(9 kg)

**Equipment furnished with each Mega-Cut machine:**

- Wooden storage container #311841
- Body gasket #47756
- Operating instructions (Form #12092)

**Equipment to be selected :**

- Drills and drill holders—page 2.15
- Shell cutters, cutter holders and pilot drills—page 2.15-2.16
- Drilling machine adapters—page 2.17