


Rev. 9-09

MUELLER D-5 Drilling Machine - for drilling operations under pressure - 5/8" to 2" inclusive


- Catalog number D-5 (Part number 39305)
- Hand or power operation
- Designed for use on pressurized or dry mains
- Used to drill through 3/4" to 2" corporation stops and service saddles
- 14"(356 mm) boring bar travel
- Has boring bar locking mechanism
- Use on cast iron or ductile iron pipe • cement lined cast iron or ductile iron pipe
• A-C pipe • PVC pipe • steel pipe • concrete pipe
- 500 psig (3447 kPa) maximum working pressure at 100 F (38 C)
- 250 F (121 C) maximum working temperature at 375 psig (2586 kPa)



NOTE: The working pressure or temperature rating is reduced accordingly if any attachment, valve, or fitting subjected to pressure or temperature during the drilling operation has a maximum working pressure or temperature rating less than that specified above.

Equipment furnished with each D-5 machine:

- Metal storage case
- Ratchet handle (85308)
- Body gasket (33278)
- Adjustable wrench (91664)
- Two double open end wrenches (58196)
- Cutting grease (88366)
- Instruction manual (Form #9335)



Equipment to be selected:

- Drills and drill holders – page 2.9
- Shell cutters, cutter holders and pilot drills – page 2.10
- Drilling machine adapter nipples – page 2.11
- Power operators – page 2.13

| | D-5 |
|-----------------------|-------------------|
| Total shipping weight | 60.5 lbs. (27 kg) |
| Machine weight only | 35 lbs. (16 kg) |