MUELLER CL-12 Drilling Machine – for drilling operations under pressure – 2" to 12" inclusive

- ❏ Catalog number CL-12 (part # 39295)
- ❏ Hand or power operation
- ❏ Designed for use on pressurized or dry mains
- ❏ Used to cut 1-3/4" to 11-1/2" holes
- ❏ Will make cuts through tapping valves from 2" to 12"
- ❏ 25" (635 mm) boring bar travel
- ❏ Use on cast iron or ductile iron pipe • cement lined cast iron or ductile iron pipe • A-C pipe • concrete pipe • steel pipe • cast iron O.D. PVC
- ❏ 250 psig (1724 kPa) maximum working pressure at 100 F (38 C)
- ❏ 500 F (260 C) maximum working temperature at 150 psig (1034 kPa)

NOTE: The working pressure or temperature rating is reduced accordingly if any attachment, valve or fitting subjected to pressure or temperature during the drilling operation has a maximum working pressure or temperature rating less than that specified above.

Equipment furnished with each MUELLER CL-12 Drilling

- ❏ Wooden storage chest (not shown)
- ❏ Ratchet handle
- ❏ Screw driver
- ❏ Double open end wrenches
- ❏ Allen wrenches
- ❏ Machine to adapter bolts and nuts
- ❏ Machine to adapter D-type washers
- ❏ Machine to adapter gasket
- ❏ Cutting grease #88366
- ❏ Instruction manual (Form # 8895)

Equipment to be selected

- ❏ Shell cutters, drills, pilot drills, arbors, and hubs – page 3.4
- ❏ Machine adapters – page 3.5
- ❏ Power operators – page 3.23

	CL-12
Total shipping weight	400 lbs. (180 kg)
Machine only weight	270 lbs. (120 kg)

WARNING: Use on A-C pipe, which contains a known carcinogen, requires appropriate protective equipment and procedures be employed.