

1-1/2" & 2" MUELLER® ORI-CORP® CORPORATION VALVES



5.7

Rev. 4-01



H-15013

MUELLER ORI-CORP Corporation Valve
Inlet: AWWA taper (MUELLER "CC") thread
Outlet: MUELLER® 110® Conductive Compression Connection for CTS O.D.* tubing

1-1/2"	2"
--------	----



H-15023

MUELLER ORI-CORP Corporation Valve
Inlet: AWWA I.P. thread
Outlet: MUELLER 110 Conductive Compression Connection for CTS O.D.* tubing

1-1/2"	2" **
--------	-------



P-15013

MUELLER ORI-CORP Corporation Valve
Inlet: AWWA taper (MUELLER "CC") thread
Outlet: MUELLER Pack Joint Connection for CTS O.D.* tubing

1-1/2"	2"
--------	----



P-15023

MUELLER ORI-CORP Corporation Valve
Inlet: AWWA I.P. thread
Outlet: MUELLER Pack Joint Connection for CTS O.D.* tubing

1-1/2"	2" **
--------	-------



H-15014

MUELLER ORI-CORP Corporation Valve
Inlet: AWWA taper (MUELLER "CC") thread
Outlet: F.I.P. thread

1-1/2" ‡	2" ‡
----------	------



H-15015

MUELLER ORI-CORP Corporation Valve
Inlet: AWWA I.P. thread
Outlet: F.I.P. thread

1-1/2" ‡	2" ‡
----------	------



H-9968

MUELLER ORI-CORP Corporation Valve
Inlet: AWWA taper (MUELLER "CC") thread
Outlet: M.I.P. thread

1-1/2"	2"
--------	----



H-9969

MUELLER ORI-CORP Corporation Valve
Inlet: AWWA I.P. thread
Outlet: M.I.P. thread

1-1/2"	2" **
--------	-------

*See charts on pages 5.12-5.16 for tubing and pipe that may be used on these connections.

** For use with Service Saddle only—cannot be machine inserted.

‡ Requires minimum ordering quantity. Contact MUELLER Customer Service Center for minimum order requirements and availability.

NOTE: Sizes shown above represent nominal size of inlet and outlet connections.

MUELLER® Corporation Valves are manufactured and tested in accordance with ANSI/AWWA C800.