


SERVICE FITTINGS WITH COPPER FLARE CONNECTION


Shaded area indicates changes Rev. 8-04



Two Part Union
Copper flare nut x female
copper flare thread

H-15405

3/4"	1"	1-1/2"	2"
------	----	--------	----



Eighth bend coupling
Copper flare nut x F.I.P.

H-15455


3/4"	1" ‡
------	------



Straight three part union
Copper flare nut—both ends

H-15400


1/2"	3/4"	3/4"x1"	1"	1-1/4"	1-1/4"x1"	1-1/2"
2"						



Quarter bend coupling
Copper flare nut x F.I.P.

H-15460

3/4"	1"	1-1/4" ‡	1-1/2" ‡	2"
------	----	----------	----------	----



Eighth bend three part union
Copper flare nut—both ends

H-15522

3/4"	1"
------	----



Straight coupling
Copper flare nut x M.I.P.

H-15425


1/2" ‡	1/2"x3/4"	3/4"	3/4"x1/2"	3/4"x1"	1"
1"x3/4"	1"x1-1/4" ‡	1-1/4"	1-1/2"	2"	



Quarter bend three part union
Copper flare nut—both ends

H-15525


3/4"	1"	1-1/2"	2"
------	----	--------	----



Quarter bend coupling
Copper flare nut x M.I.P.

H-15530


1/2" ‡	3/4"	1"	1"x3/4"	1-1/2" ‡	2"
--------	------	----	---------	----------	----



Straight coupling
Copper flare nut x F.I.P.

H-15450

1/2"	1/2"x3/4" ‡	3/4"	3/4"x1/2"	1"	1"x3/4"	1-1/4"	1-1/2"	2"
------	-------------	------	-----------	----	---------	--------	--------	----



Eighth bend coupling M.I.P.
x copper flare nut

H-15539

3/4"	1"
------	----

NOTE: Sizes shown above represent normal size of fitting. When two sizes are given, the first is size of copper flare nut and second is size of threaded end.

‡ Requires minimum ordering quantity. Contact MUELLER Customer Service Center for minimum ordering requirements and availability.

MUELLER Service Fittings are manufactured and tested in accordance with ANSI/AWWA C800