


6.4



SERVICE FITINGS WITH COPPER FLARE CONNECTION

Rev. 9-09 Shaded area indicates changes



Eighth bend coupling
Swivel nut with female
copper flare thread x cop-
per flare nut

H-15064


3/4"	1"
------	----



Eighth bend coupling
Swivel nut with female
MUELLER® Coupling
thread x copper flare nut

H-15486

1/2"x3/4"	5/8"x3/4"	3/4"	1"
-----------	-----------	------	----



Quarter bend coupling
Swivel nut with female
copper flare thread x cop-
per flare nut

H-15069


3/4"	1"	1-1/2"	2"
------	----	--------	----



Quarter bend coupling
Swivel nut with female
MUELLER Coupling
thread x copper flare nut

H-15491

1/2"x3/4"	5/8"x3/4"	3/4"	1"
-----------	-----------	------	----



Eighth bend coupling
Swivel nut with female
increasing I.P. thread (this
thread is one size larger
than nominal size of fit-
ting) x copper flare nut

H-15471


3/4"	1"‡
------	-----



Straight coupling Female
copper flare thread x cop-
per flare nut

H-15062


3/4"x1"	1"x3/4"	1"x1-1/4"
---------	---------	-----------



Quarter bend coupling
Swivel nut with female
increasing I.P. thread (this
thread is one size larger
than nominal size of fit-
ting) x copper flare nut

H-15476

3/4"	1"
------	----



Eighth bend coupling
Female copper flare thread
x copper flare nut

H-15063

3/4"	1"	1-1/2"	2"
------	----	--------	----

Note: Sizes shown above represent nominal size of fitting. When two sizes are listed, the first is the size of threaded end and the second is size of copper flare nut. ‡Requires minimum ordering quantity. Contact MUELLER Customer Center for minimum order requirements and availability.

MUELLER Service Fittings are manufactured and tested in accordance with ANSI/AWWA C800.