


# GROUND KEY ANGLE METER VALVES

## 3/4" & 1"



Ground key angle meter stop  
**MUELLER 110<sup>®</sup> Conductive**  
 Compression Connection for CTS  
 O.D.\* tubing x meter swivel nut\*\*  
 180° turn check - lock wing

### H-14258

Catalog size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Pipe size	3/4	3/4	1	1



Ground key angle meter stop  
**MUELLER<sup>®</sup> Pack Joint Connection**  
 for CTS O.D.\* tubing x meter  
 swivel nut\*\*  
 180° turn check - lock wing

### P-14258

Catalog size	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Tubing size	3/4	1	1



Ground key angle meter stop  
**MUELLER 110 Compression**  
 Connection for IPS PE\* plastic pipe  
 x meter swivel nut\*\*  
 180° turn check - lock wing

### H-14259

Catalog size	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Pipe size	3/4	1	1



Ground key angle meter stop  
**MUELLER INSTA-TITE<sup>®</sup>**  
 Connection for IPS PE\* plastic  
 pipe x meter swivel nut\*\*  
 180° turn check - lock wing

### H-14266

Catalog size	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Pipe size	3/4	1	1



Ground key angle meter stop  
**MUELLER INSTA-TITE<sup>®</sup>**  
 Connection for CTS O.D.\* PE  
 plastic tubing x meter swivel nut\*\*  
 180° turn check - lock wing

### H-14267


Catalog size	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Pipe size	3/4	1	1



Ground key angle meter stop  
**Copper flare nut x meter swivel**  
 nut\*\*  
 180° turn check - lock wing

### H-14255

Catalog size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Tubing size	3/4	3/4	1	1



Ground key angle meter stop  
**F.I.P. x meter swivel nut\*\***  
 180° turn check - lock wing

### H-14265

Catalog size	5/8x3/4	5/8x3/4x3/4	5/8x3/4x1	1
Meter size	5/8	5/8x3/4, 3/4	5/8x3/4, 3/4	1
Pipe size	3/4	3/4	1	1

\* See charts on pages 8D.17 and 8D.18 for tubing and pipe that can be used with this connection.

\*\* Meter swivel nuts are regularly furnished with a saddle feature to aid in meter installation and removal. A plain swivel nut is available as an option by adding a suffix of -1 to the catalog number.