

IN-LINE CHECK VALVES



H-14241

Straight dual check valve
Inlet: M.I.P.
Outlet: F.I.P.
 To order ASSE approved†† model add suffix -A to catalog number

| | | |
|--------------|---------------|---|
| Catalog size | 3/4x1 †† | 1 |
| Pipe size | 3/4 in, 1 out | 1 |



H-14243

Straight dual check valve
Inlet: F.I.P.
Outlet: F.I.P.
 To order ASSE approved†† model add suffix -A to catalog number

| | | | | | |
|--------------|-----|---------------|---|---------------|---------|
| Catalog size | 3/4 | 3/4x1 †† | 1 | 1-1/2 ††, ††† | 2 †, †† |
| Pipe size | 3/4 | 3/4 in, 1 out | 1 | 1-1/2 | 2 |



H-14242

Straight dual check valve
Inlet: Meter swivel nut*
Outlet: F.I.P.
 To order ASSE approved model add suffix -A to catalog number

| | | | | | |
|--------------|--------------|--------------|---|---------------|----------|
| Catalog size | 5/8x3/4x3/4 | 5/8x3/4x1†† | 1 | 1-1/2 ††, ††† | 2 †, †† |
| Meter size | 5/8x3/4, 3/4 | 5/8x3/4, 3/4 | 1 | 1-1/2 | 1-1/2, 2 |
| Pipe size | 3/4 | 1 | 1 | 1-1/2 | 2 |



H-14283

Straight dual check valve
Inlet: M.I.P.
Outlet: MUELLER 110 Conductive Compression Connection for CTS O.S. ** tubing.
 To order ASSE approved†† model add suffix -A to catalog number

| | |
|--------------|-----|
| Catalog size | 3/4 |
| Pipe size | 3/4 |



H-14282

Straight dual check valve
Inlet: M.I.P.
Outlet: M.I.P.
 To order ASSE approved†† model add suffix -A to catalog number

| | |
|--------------|-----|
| Catalog size | 3/4 |
| Pipe size | 3/4 |

* Meter swivel nuts are regularly furnished with a saddle feature to aid in meter installation and removal. A plain swivel nut is available as an option by adding a suffix of -1 to the catalog number.

** See charts on page 8D.17 and 8D.18 for tubing and pipe that can be used with this connection.

†These valves have meter flanges double drilled to fit either 1-1/2" or 2" meters.

††These 3/4"x1", 1-1/2" and 2" sizes are not available as ASSE approved.

†††These have meter flanges for 1-1/2" meters