

# MARKETING NEWS

New products and developments from the Leading Supplier of Water Distribution Products

## Website New Features

Ever wonder how many inches of machine travel are need to complete an 8" tap on 12" ductile iron pipe? This information is now available 24/7 on our website [www.muellercompany.com](http://www.muellercompany.com). In our "Information/Downloads" section under the "manuals" tab we have added the travel charts for our large drilling machines on ductile iron and plastic pipe. Also in the Download area but under the "Bulletins" tab, you can now find several new types of information, including Material Safety Data Sheets (MSDS), hydrant and gate valve troubleshooting, and FAQs pertaining to our machines and power operators.

## 2361 Series RW Valve Offering Extended

As the need for large distribution lines grow so does the size of our valve product offering. We have recently completed the roll out of our 42" and 48" resilient wedge gate valves. These valves have our standard 250 psig working pressure and are available in MJ x MJ, FL x FL, FL x MJ, and as a tapping valve. They are offered with bevel or spur gearing and optional bypass valve. We also have added 14" and 16" OS&Y valves to meet the needs of plant and vault applications. Contact your local distributor for availability for your project.



## Additional Tap Size Now Available for the Stainless Tapping Sleeves

We have recently added the 3" stainless steel flange outlet to the product offering of the H300 and H304 Stainless Steel Tapping sleeves. Contact your Local Mueller Pipe Repair Products Distributor for price and availability.



## Our Brass Selection Grows Again

We continue to add new brass items to our extensive offering. Here's a list of the latest new items.

### Service Brass

H10076	3/4"	FIP x FIP 1/8th bend
H10095	1-1/2" & 2"	Increasing FIP X MIP 1/8th bend
H10097	3/4" & 1"	FIP tee
H15069	3/4" x 1"	Female Copper Service Swivel x Copper Flare 90° elbow
H15076	3/4" x 1"	Female Copper Service Swivel x CTS 110 90° elbow
H15098	3/4" & 1"	Corporation valve coupling Mueller Coupling Thread x MIP
H15343	1" x 2"	CTS 110 WYE
H15354	3/4" x 1"	IPS 110 x IPS 110 WYE branch (4 piece construction)
H15363	1 1/2" x 1" x 7 1/2"	CTS 110 inlet x MIP outlet U-branch
H15363	1" x 1" x 13-1/2"	CTS 110 inlet x MIP outlet U-branch
H15383	3/4" & 1" tee	FIP x FIP run x CTS 110 tee
H15392	3/4" & 1" tee	CTS 110 x FIP run x FIP tee
H15428	1/2" x 2"	CTS 110 x 2" MIP
H15460	1" x 3/4"	Flare x FIP 90° elbow
H15460	3/4" x 1"	Flare x FIP 90° elbow
H15481	3/4"	Mueller® Coupling thread x CTS 110
H15491	3/4" x 1"	Female Mueller® Coupling Thread Swivel x Copper Flare 90° elbow
H15494	2" x 1-1/2"	MIP x FIP Straight Reducing Coupling
H15525	3/4" x 1"	Copper Flare x Copper Flare 90° elbow
H15526	1" x 3/4"	CTS PJ x CTS PJ 90° elbow
H15526	3/4" x 1"	CTS PJ x CTS PJ 90° elbow
H15530	1" x 3/4"	Copper Flare x FIP 90° elbow
H15530	3/4" x 1"	Copper Flare x FIP 90° elbow
H15531	1" x 3/4"	CTS 110 x FIP 90° elbow
H15531	3/4" x 1"	CTS 110 x FIP 90° elbow
P15076	3/4" x 1"	Female Copper Service Swivel x CTS PJ 90° elbow
P15343	1" x 2"	CTS 110/PJ WYE (2 piece construction)
P15363	1-1/2" x 1" x 7-1/2"	CTS PJ inlet x MIP outlet U-branch
P15526	3/4" x 1"	CTS 110 x CTS 110 90° elbow
P15531	1" x 3/4"	CTS PJ x FIP 90° elbow
P15531	3/4" x 1"	CTS PJ x FIP 90° elbow
P15533	1" x 3/4"	CTS 110 x MIP 90° elbow
P15533	3/4" x 1"	CTS 110 x MIP 90° elbow
V15446	1"	Flare x PVC PJ straight coupling

"CTS 110" refers to the Mueller 110° Compression Connection for CTS tubing.

## Machines

We now offer PVC/PEP shell cutter kits for your CL-12™ or C1-36™ machine needs. These kits come with shell cutters, pilot shell cutters and extensions to accomplish cuts through 4" – 12" valves. The cutters will accommodate PVC pipe and PEP pipe to DR9 thicknesses. Order kit number 682662 for the CL-12 machine or kit number 682623 for the C1-36 machine and you will be ready to go.

Mueller Cutting Grease is now available in a 1 gallon can P/N 83486.



## Brass Insulated Product Offering Expanded

To help protect your distribution system from stray current corrosion we have added 2" ball corporation valves and ball curb valves to our existing 3/4" and 1" insulated product offering.

The following products are now available:

N35008/N35028 CC/MIP x CTS 110;

N30046/N30045 CC/MIP x FIP;

N35209 CTS 110 x CTS 110.

To drill through the corporation valves with your D-5™ use adapter 682649. To use your E-5™ or MegaCut™ machines use adapter 502938 along with 682649.



## Our Brass Selection Grows Again cont.

### Brass Valves

681228	Lock Open FIP ground key angle for 5/8 x 3/4" and 3/4" meters
B24279	5/8" x 3/4" x 3/4" IPS 110 x Locknut angle ball valve
B24279	1" IPS 110 x Locknut angle ball valve
B25085	1" CC Thread x CTS 110 ball curb
B25130	3/4" CTS 110 x FIP full port ball curb with 4" lay length for retro-fit
B25130	1" CTS 110 x FIP full port ball curb valve with 5" lay length for retro-fit
B25168	3/4" Copper Flare x FIP ball curb 4-3/16" lay length for retro-fit
E24279	5/8" x 3/4" x 3/4" IPS PJ x Locknut angle ball valve
E25211	1" PEP x PEP Ball curb (2 piece construction)
V25226	1" PVC x PVC Ball curb (2 piece construction)

### Meter Brass

H10896	5/8" x 3/4"	Meter Saddle Nut x MIP straight coupling
H14200	5/8" x 3/4" x 1"	Meter Swivel Nut x Copper Flare 90° elbow
H14201	5/8" x 3/4" x 3/4"	Straight Meter Coupling for 5/8" x 3/4" or 3/4" meters x CTS 110
H14202	5/8" x 1"	Iron bar Lock nut x Copper Flare 90° elbow
H14202	5/8" x 3/4" x 1"	Iron bar Lock nut x Copper Flare 90° elbow
H14206	5/8" x 3/4" x 1"	Meter Swivel Nut x CTS 110 90° elbow
H14207	5/8" x 3/4" x 1"	Iron Bar Lock nut x CTS 110 90° elbow
H14480	5/8" x 3/4" x 3/4"	(2.50" length) & 1" (3" length) with Single check
H14490	5/8" x 3/4" x 3/4"	(2.50" length) Straight Coupling
H14490	1"	(3" length) with Dual check Straight Coupling
P14206	5/8" x 3/4" x 1"	Meter Swivel Nut x CTS PJ 90° elbow
P14207	5/8" x 3/4" x 1"	Iron Bar Lock nut x CTS PJ 90° elbow
H14269	2" Angle Dual Check Valve	Meter Flange x CTS 110 (2 piece construction)

### New setters / setter adapters:

B2498	1" CTS 110 x 1" FIP for 5/8" x 3/4" or 3/4" meters
H14227	Multipurpose thread x 1" CTS 110

*"CTS 110" refers to the Mueller 110° Compression Connection for CTS tubing.  
"IPS 110" refers to the Mueller 110° Compression Connection for IPS pipe.*