



Rev. 8-04



H-15373

Inlet: MUELLER® 110®
Conductive Compression
Connection for CTS O.D.*
tubing
Outlets: MUELLER 110
Conductive Compression
Connection for CTS O.D.*
tubing straight line


1"x3/4"x7-1/2"	1-1/2"x3/4"x7-1/2" ‡
----------------	----------------------



P-15373

Inlet: MUELLER Pack Joint
Connection for CTS O.D.*
tubing
Outlets: MUELLER Pack
Joint Connection for CTS
O.D.* tubing straight line


1"x3/4"x7-1/2"	1-1/2"x3/4"x7-1/2" ‡
----------------	----------------------



H-15363

Inlet: MUELLER 110
Conductive Compression
Connection for CTS O.D.*
tubing
Outlets: M.I.P. thread
straight line


3/4"x3/4"x7-1/2"	1"x3/4"x7-1/2"	1"x3/4"x6-1/2"	1"x3/4"x13-1/2"
1"x1"x7-1/2"	1-1/2"x3/4"x7-1/2"	1-1/2"x1"x7-1/2"	



P-15363

Inlet: MUELLER® Pack Joint
Connection for CTS O.D.*
tubing
Outlets: M.I.P. thread
straight line


3/4"x3/4"x7-1/2"	1"x3/4"x7-1/2"	1"x3/4"x13-1/2"
1-1/2"x1"x7-1/2"		



H-15369

Inlet: MUELLER 110
Conductive Compression
Connection for CTS O.D.*
tubing
Outlets: M.I.P. threads right
angle

1"x3/4"x7" ‡



H-15360

Inlet: Copper flare nut
Outlets: Copper flare nut
straight line

1"x3/4"x10"



H-15362

Inlet: Copper flare nut
Outlets: M.I.P. thread
straight line

3/4"x3/4"x7"	3/4"x3/4"x7-1/2"	3/4"x3/4"x13-1/2"	1"x3/4"x6-1/2"
1"x3/4"x7"	1"x3/4"x7-1/2"	1"x3/4"x13-1/2"	



H-15368

Inlet: Copper flare nut
Outlets: M.I.P. thread right
angle

3/4"x3/4"x7" ‡	1"x3/4"x7" ‡
----------------	--------------

NOTE: Inline or Angle valves with fip threads can be added to any U Branch with MIP Ends

‡Requires minimum ordering quantity. Contact MUELLER Customer Service Center for minimum ordering requirements and availability.

* See page 6.29 for tubing that can be used with this connection.

NOTE: Sizes shown above represent nominal size of end connections. First is size of inlet, second is size of outlets, and third is center-to-center dimension between outlets.

MUELLER "U" Branch Connections are manufactured and tested in accordance with ANSI/AWWA C800.