



Brass plug - Machine inserted*
AWWA taper
(MUELLER "CC") thread

H-10034

1/2"±	5/8"	3/4"	1"	1-1/4"±	1-1/2"	2"
-------	------	------	----	---------	--------	----



Brass plug - Machine inserted*
I.P. thread

H-10037

3/4"±	1"±	1-1/4"±	1-1/2"±	2"±	2-1/2"±
-------	-----	---------	---------	-----	---------



Brass bushing
Male AWWA taper
(MUELLER "CC") thread x
female AWWA taper
(MUELLER "CC") thread

H-10036

1"x3/4"	1-1/2"x1"	2"x3/4"	2"x1"	2"x1-1/2"
---------	-----------	---------	-------	-----------



Brass plug** - Square head with
AWWA taper
(MUELLER "CC") thread

H-10033

1/2"	5/8"	3/4"	1"	1-1/4"	1-1/2"	2"
------	------	------	----	--------	--------	----



Brass plug** - Square head with
I.P. thread

H-10035

1/2"±	3/4"	1"	1-1/4"±	1-1/2"±	2"±
-------	------	----	---------	---------	-----



Brass Bushings

- 47162** 1-1/4" MIP x 1" FIP
- 47163** 2" MIP x 3/4" FIP
- 47164** 2" MIP x 1" FIP
- 47165** 1" MIP x 3/4" FIP
- 47168** 1-1/2" MIP x 3/4" FIP
- 47169** 1-1/2" MIP x 1" FIP
- 47172** 2" MIP x 1-1/2" FIP