




Multi - purpose thread ends
(H-1414 shown)



Typical installation of a straight line inlet and outlet copper meter yoke

Copper meter yokes with straight line inlet and outlet, and multi-purpose thread ends

Catalog number	H-1414	H-1415	H-1418	H-1419	B-2418	B-2419
Description	Plain yoke	With test valve	With lock wing ground key angle meter stop	With lock wing ground key angle meter stop and test valve	With lock wing MUELLER 300™ Angle Ball Valve*	With lock wing MUELLER 300 Angle Ball Valve* and test valve



M-98™ ASSE approved top entry vertical check


Check valve options

MUELLER Copper Meter Yokes can be ordered with one of the following: an ASSE approved top entry vertical check valve; an ASSE approved dual check valve; a dual check valve (ASSE non-approved). To order the ASSE approved top entry check feature, add a suffix of **-6A** to the yoke catalog number; add **-6D** for the same check with a test drain. For the dual check feature, add a suffix of **-2A** to the yoke catalog number for the ASSE approved model or **-2** suffix for the nonapproved model. Examples: **H-1414-6D** for the ASSE approved top entry vertical check with a test drain; **H-1414-2A** for the ASSE approved model angle dual check valve.



Angle dual check valve

Dimensions



Meter size	5/8"*	5/8" x 3/4"*	3/4"*
Nominal size of I.P. thread in meter nut	3/4"	1"	1"
Dimension A	1-1/16"	1-5/16"	1-5/16"
Dimension B	7-7/8"	7-7/8"	9-3/8"
Dimension C - nominal pipe size of inlet and outlet	3/4"	3/4"	3/4"
Dimension D	14-3/8"	14-3/8"	15-7/8"
Dimension E	4-9/16" (7"**)	4-9/16" (7" **)	4-9/16" (7" **)

* Add "R" to the end of the yoke catalog number to order a reduced port Angl Ball Valve: EXAMPLE: 5/8x3/4x7 B-2418R.

** With 6A or 6D option.

Copper Meter Yokes are normally supplied less end connections. Copper space bar available. See pages 8A.48 and 8A.49 for end connections that can be used with these yokes.

SPECIFY METER SIZE AND CATALOG NUMBER.