

Rev. 8-04 Shaded area indicates changes

- ❑ **Super Centurion 250™ 3-way catalog numbers**
(approved to UL 246, FM 1510, ANSI/AWWA C502 Standards) -
 - A-421 4-1/2" main valve opening three way (two hose nozzles and one pumper nozzle)
 - A-423 5-1/4" main valve opening three way (two hose nozzles and one pumper nozzle)
 - Super Centurion 200™ 2-way catalog numbers**
(approved to ANSI/AWWA C502 Standards) -
 - A-420 4-1/2" main valve opening two way (two hose nozzles)
 - A-422 5-1/4" main valve opening two way (two hose nozzles)
 - A-425 5-1/4" main valve opening two way (two pumper nozzles)
 - Super Centurion 200™ 1-way catalog number**
(approved to ANSI/AWWA C502 Standards)-
 - A-424 4-1/2" main valve opening one way (one pumper nozzle)
- ❑ 10 year limited warranty on material and workmanship
 - ❑ Meets all applicable parts of ANSI/AWWA C502 Standard
 - ❑ Post type dry barrel design
 - ❑ Dry top design with O-ring sealed oil reservoir
 - ❑ Traffic feature with stainless steel safety stem coupling
 - ❑ Compression-type main valve closes with pressure for positive seal; it is made of rubber and is conveniently reversible providing a spare for long service life
 - ❑ Operating nut available in wide variety of shapes and sizes-open left or right
 - ❑ Field replaceable hose and pumper nozzles
 - ❑ Hose and pumper nozzles have large radius, full flow openings for low friction loss
 - ❑ Contoured shoe is designed for full flow
 - ❑ Dual bronze drain valves provide effective barrel drainage
 - ❑ 250 psig (1723 kPa) maximum working pressure, 500 psig (3447 kPa) static test pressure for 3-way hydrants;
200 psig (1379 kPa) maximum working pressure, 400 psig (2758 kPa) static test pressure for 2-way and 1-way hydrants



Dimensions

