# MUELLER® Series R-2361-6 OS&Y Resilient Wedge Valve

#### 18" – 24" • Ductile Iron • 175 PSIG Working Pressure

#### **Forged Bronze Stem**

Superior strengthened stem for less maintenance.

## **Guide Cap Bearings**

Guide cap bearings are made of polymer and snapped over rubber covered wedge guides, provide bearing surfaces that protect both wedge and interior body coating from wear and aid in easy operation – even the largest valves installed horizontally. Rollers, tracks or scrapers are not needed.

#### 100% Elastomer Encapsulated Wedge

No thin spots, voids or uncoated areas for superior corrosion resistance.

## **Epoxy Coating**

Superior fusion-bonded powder epoxy inside and out, 10 mils nominal. AWWA C550 compliant.

## **UL Listed**

Rated at 175 PSIG maximum working pressure. Hydrostatically tested at 500 PSIG. NSF 61 certified.

#### American Made Quality

Made in Chattanooga, Tennessee plant certified to ISO 9001.

#### Flat Bottom Surfaces

Stands upright for easier handling and storage.

## **Mueller 10 Year Limited Warranty**

.



Customer Service – Decatur, IL Water Division : 800-423-1323 www.muellercompany.com Canada – Mueller Canada Inc., Barrie, Ontario 705-719-9965

Form 12695 - 2/11

All products must be installed and maintained in accordance with applicable instructions and/or standards. Copyright 2011 Mueller Co.