Remote Pressure Monitoring - Quick Start Guide Valve Box Installation Instructions

HYDRO-GUARD



Verify Cell Coverage at Installation Site.

eration.


eration.

Place cell phone of same carrier (Verizon or AT&T) at the planned installation location, and verify the signal quality. Indicator must have a minimum of two (2) bars.


Appl of pr

Thre


Insta



Install service saddle.



Install guide plate.



Thread corporation valve into service saddle. Valve should be open.



5 Perform drilling operation.



6 Apply joint-sealant, dry the connection inlet before inserting the pressure sensor; and then thread pressure sensor into corporation valve. Open Valve



Insta asse


> Install adjustable top into Plug sensor cable into R nut 1/4 turn counterclock RTU into adjustable top. back fill and pave area a box per direction by eng record.

> Pressure monitoring beg




Install adjustable top into Plug sensor cable into R nut 1/4 turn counterclock RTU into adjustable top. back fill and pave area a box per direction by eng record.

Pressure monitoring beg onto www.miwt.net to vie




Install valve box over the assembly.




onto www.miwt.net to vit 8 Carefully back fill and pave area around valve box per direction by engineer of record. Be sure to keep the sensor connector within reach.



DO NOT PAVE OVER RTU!





9 Plug sensor cable into Black connector on RTU and hand tighten connector. Insert RTU into adjustable top. Be certain lid of RTU is flush with valve box frame.


10 Record Location (see reverse side)

Bracket Installation Instructions




Verify Cell Coverage at Installation Site.


Place cell phone of same carrier (Verizon or AT&T) at the planned the signal quality. Indicator must have a minimum of two (2) bars. Place cell phone of same carrier (Verizon or AT&T) at the planned installation location, and verify



2 Apply joint-sealant and thread pressure sensor into 1/4" NPT port. Turn on the water.



Install mounting bracket to wall of meter box/vault.



Plug sensor cable into RTU and rotate nut 1/4 turn counter-clockwise.

Sticker with serial number goes here

IMPORTANT: Please record location of installation and return this document to administrator named on the shipping label of this package.

| Address: | | |
|-----------------------------|------------|--|
| | | |
| GPS location (if available) | | |
| Latitude: | Longitude: | |
| Installed by: | Date: | |



Mueller Co. LLC 1200 Abernathy Rd., Suite 1200 Atlanta, GA 30328

www.muellercompany.com moreinfo@muellercompany.com Phone: 1.423.209.4800 Toll Free: 1.800.423.1323 Canada: 1.705.719.9965

Copyright © 2017 Mueller Co., LLC. All Rights Reserved.