

MUELLER

HYDRO-GUARD[®] CONTRIBUTES SUBSTANTIAL TIME AND MONEY SAVINGS, ENVIRONMENTAL SAFETY AND WATER QUALITY AT HALIFAX WATER

Case Study

PROJECT:

Halifax Regional
Water Commission

LOCATION:

Cole Harbour Road,
Dartmouth, Nova Scotia

PRODUCTS:

Hydro-Guard 200 Series Cold¹
LongNeck™ Sub-Surface
Direct Discharge Automatic
Flushing System

SCOPE

Nova Scotia's Halifax Regional Water Commission (HRWC), also known as Halifax Water, provides potable water, wastewater and stormwater services to the Halifax Regional Municipality.

Halifax Water currently manages eight watersheds as well as three groundwater sources which collectively supply potable water to over 86,000 customers. Water is delivered via 82,334 service connections—31,878 of which are located within its east region. Included within the WDS are 23 Dept. of Environment sampling stations.



PROBLEM

One of the sampling stations is located in a park on Cole Harbour Road, serviced by the Lake Major Water Supply Plant. Until 2011, water flowed regularly through a 14-inch transit line with a 2-inch connection to a car wash located prior to the dead end of the line. Toward the end of 2011 the car wash closed resulting in a decrease in low chlorine residuals due to non-movement in the main. Stimulating water movement required two HRWC staff to show up on-site for up to two hours, sometimes twice a week, to partially open a hydrant. This method flushed up to 50 m³ at a cost of \$150.00 to \$175.00 per visit. Of course non-revenue water usage increased as well.

SOLUTION

To help solve the water quality issue economically, HRWC's East Water Services Superintendent, Dave Hiscock, directed removal of the hydrant and installation of a Mueller Hydro-Guard 600 Series² Automatic Flushing System in its place. Subsequently, although the 600 Series² Flushing System resulted in far fewer man-hours at the site, water continued running down the street during flushing. Contemplation of winter climate severity issues necessitated looking into the installation of the Mueller Hydro-Guard 200 Series Cold¹ LongNeck Sub-Surface Direct Discharge Unit as the ultimate solution, as it has the capability of flushing, de-chlorinating and expelling the water into a storm sewer in an environmentally safe manner. Additionally, keeping water out of the street enhances public perception.

Installation was completed in June 2013, after an experimentation program by Halifax Water's water quality section, using a portable unit to determine optimal flush times. Hiscock reports that HRWC has reduced man-hours down to one visit per month to

check the de-chlorination pucks and ensure battery strength. The Hydro-Guard 200 Series Cold¹ Automatic Flushing System's battery has provided three years of trouble-free automatic operation vs. manual flushing. HRWC programmed their Hydro-Guard 200 Series Cold¹ Automatic Flushing System to flush for one hour twice a day (at 10 m³ per thirty minutes) vs. their former one-hour flush duration. A further reduction in flush times is anticipated since there has been no variation in chlorine residuals with the 200 Series Cold¹ Automatic Flushing System in place. Also, little maintenance has been required since installation. The only variances of this installation are extra insulation called for by HRWC, plus the appealing rock enclosure which helps the unit blend desirably with its park location.

Labor costs per flush remain at \$175.00; however, average visits to the flush site per month are down from eight to one—a savings of \$1225.00 per month. Water use per flush immediately fell from 52 m³ to 10 m³ which, when calculated over the two-year period, shows a decrease in non-revenue water use from 12,480 m³ to 9,000 m³, a 3,480 m³ savings. Aggregate costs have fallen from \$42,000 to \$24,750 within the past two years—a total savings of \$17,250 after installation.

CONCLUSION

Savings in the two years since installation of the Mueller Hydro-Guard 200 Series Cold¹ Automatic Flushing System have been substantial with over 51% in costs saved and over 32% less water loss. The cost of installation included the unit, labor and reinstatement. The cost of reinstatement comprised about half of the total cost; therefore, picking the optimal location is highly recommended. The investment has already been returned and installation of more Hydro-Guard 200 Series Cold¹ Automatic Flushing System units is contemplated. Halifax Water's forward-looking Business

ABOUT MUELLER

Mueller (NYSE:MWA) is a leading manufacturer and marketer of products and services used in the transmission, distribution and measurement of water in North America. Our broad product and service portfolio includes engineered valves, fire hydrants, metering products and systems, leak detection and pipe condition assessment. We help municipalities increase operational efficiencies, improve customer service and prioritize capital spending.

For more information about Mueller or to view our full line of water products, please visit www.muellerwp.com or call Mueller customer service at 1.800.423.1323.

Mueller refers to one or more of Mueller Water Products, Inc. (MWP), a Delaware corporation, and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. Mueller brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, HYMAX®, i2O®, Jones®, Krausz®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands to learn more.

© 2021 Mueller Water Products, Inc. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details visit www.mwppat.com.

Plan includes a commitment to continuous improvement and ensures that the system's technology and capacity will serve its communities into the future years of growth and expansion.

REFERENCES

1. Hiscock, Dave, Halifax Water. Phone interview, 3 November 2015.
2. Hiscock, Dave, "The 200 Series Cold¹ Automatic Flushing System", Halifax Water, 6 November 2015.
3. Halifax Regional Water Commission, Section 2-01 Environmental Policy ISO 14001: 4.2, February 2013.
4. Halifax Regional Water Commission Eighteenth Annual Report, 31 March 2014.
5. Halifax Regional Municipality, Source Water Protection, 8 December 2015.

¹The Hydro-Guard® 200 Series Cold Automatic Flushing System was previously referred to as the Hydro-Guard HG-4 Automatic Flushing System.

²The Hydro-Guard® 600 Series Automatic Flushing System was previously referred to as the Hydro-Guard® HG-6 Automatic Flushing System.