

## MFP2 RESILIENT WEDGE GATE VALVE FULL WALL 300PSI. 2"-12"

## **Suggested Specifications**

- 1. The resilient seat gate valves shall be UL 262 listed and FM 1120/1130 approved.
- 2. The valve shall have a 300psig working pressure.
- 3. The valve type shall be OS&Y (outside screw & yoke).
- 4. The valve shall have an arrow cast on the handwheel showing opening direction. The direction of opening shall be as specified.
- 5. The valves shall have Type 316 stainless steel bolts and nuts for the bonnet/yoke combo. Nuts for the glands shall be silicon bronze.
- 6. The valve stem shall be made of stainless-steel ASTM 276 material. The stem material shall provide a minimum 25,000psi tensile strength with 20% elongation and yield strength of 95,000psi.
- 7. The valve body and bonnet/yoke combo shall be composed of ASTM A536 ductile iron.
- 8. The valve disc and guide lugs must be fully (100%) encapsulated in EPDM ASTM D2000 rubber material. Guide caps of an acetal bearing material shall be placed over solid guide lugs to prevent abrasion and to reduce the operating torque.
- 9. The valves shall have all internal and external ferrous surfaces coated with a fusion bonded thermosetting powder epoxy coating of 10 mils nominal thickness. The coating shall conform to AWWA C550.
- 10. The valves shall be warranted by the manufacturer against defects in materials or workmanship for a period of ten (10) years from the date of manufacture. The manufacturing facility for the valves must have current ISO certification.
- 11. The OS&Y valves shall be Mueller RMFP2 (2"-12") or approved equal.

For more information about us, or to view our full line of products, please visit www.mueller-international.com or call International Customer Service at:

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro-Guard®, Jones®, Krausz®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands to learn more.

Copyright © 2022 Mueller Water Products, Inc. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details visit <a href="https://www.mwppat.com">www.mwppat.com</a>.

F 13814 2/22

MUELLER