




| ITEM NO | PART NUMBER | QTY | DESCRIPTION | MATERIAL |
|---------|--------------|-----|---|---|
| 1 | 526423 | 1 | COPPER SPACER TUBE | COPPER TUBING ASTM B75 UNS C1220, H80 TEMPER |
| 2 | 215B2426551N | 1 | 5/8" X 3/4" FULL PORT BALL VALVE | LEAD FREE BRASS ALLOY ASTM B584 C89833/C87850 |
| 3 | 215H14223N | 2 | 3/4" MULTI-PURPOSE X 3/4" MIP TAILPIECE | LEAD FREE BRASS ALLOY ASTM B584 C89833/C87850 |
| 4 | 215H14244 | 1 | 5/8" X3/4" DUAL CHECK VALVE | LEAD FREE BRASS ALLOY ASTM B584 C89833/C87850 |
| 5 | 333H15451N | 2 | 3/4" FIP X 1" 110 CTS COMP. TAIL PIECE | LEAD FREE BRASS ALLOY ASTM B584 C89833/C87850 |
| 6 | 527354E | 2 | 5/8" X 3/4" METER YOKE BODY | LEAD FREE BRASS ALLOY ASTM B584 C89833/C87850 |

OPTION CODE: 24

*1" x 3/4" 015451 INSTALLED ON INLET AND OUTLET

| | | | | | | |
|--|--|----------|------|---|---|--------------|
| INTERPRET THIS DRAWING IN ACCORDANCE WITH ASME Y14.5 2018 | | NAME | DATE | THIRD ANGLE PROJECTION  |  | |
| | | DRAWN BY | AOS | | | May-20-2025 |
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. MACHINING TOLERANCES: .X ±.1 .XX ±.015 .XXX ±.005 ANGULAR CORNER BREAK FINISH ±1° .015/.025 125 µin. RA | D.E. APPR. | | | TITLE: 5/8"X3/4" COPPER METER SETTER LEAD FREE BRASS | | |
| | M.E. APPR. | | | | | |
| | Q.A. APPR. | | | | | |
| | | | | | | |
| | DO NOT SCALE DRAWING | | | | | |
| |  = CRITICAL () = REFERENCE | | | | | |
| MATERIAL: | | | | SIZE | DWG. NUMBER | REV |
| | | | | B | 203B24180-2-24N | |
| STK NUMBER: | REF.NO. | | | SCALE: | WT: | SHEET 1 OF 1 |

| REVISIONS | | | | | |
|-----------|-----|-----------------|----------|---------|----------|
| REV | ECR | DESCRIPTION | DRAWN BY | DATE | APPROVED |
| A | | DRAWING CREATED | AOS | 5/20/25 | |

TITLE TO AND OWNERSHIP OF THIS ENGINEERING DATA REMAINS IN Mueller Co. ASSENT ON THE PART OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED.