



110[®] COMPRESSION CONNECTIONS FOR WATER USE (CONDUCTIVE)

1. MATERIAL SPECIFICATIONS

- 1.1 **Nut** – Cast Bronze, ASTM B-62.
- 1.2 **Nut Interior Coating** - Amide Wax.
- 1.3 **Gasket** - Rubber - ASTM D2000 SBR.
- 1.4 **Gripper Band** - Hardened Stainless Steel - Type 410.
- 1.5 **Body** - Cast Bronze - ASTM B584 C89833.
- 1.6 **Gasket Conductor Spring** (CTS only) – Bronze Wire - ASTM B134 Alloy C26000.
- 1.7 **Rigid Metal Liner** (for use with plastic pipe or tubing) - Stainless Steel - ANSI Type 304.

2. SIZES, OPERATING PRESSURE & OPERATING TEMPERATURE

- 2.1 Two basic styles of connections are available.
 - 2.1.1 Connections are available for 1/2”, 3/4”, 1”, 1-1/4”, 1-1/2”, and 2” Copper Tube Size (CTS O.D.) Tubing. See chart below.
 - 2.1.2 Connections are available for 3/4” and 1” Iron Pipe Sizes (IPS I.D.) – PE Plastic Pipe. See chart below.
- 2.2 **Operating Pressure** - The pressure holding capability of the Mueller 110 Compression Connection is designed to be greater than that of the valve or fitting on which it is used (only in potable water distribution applications complying with AWWA standards).
- 2.3 **Operating Temperature** - range is +32F to +150F.

TUBING & PIPE DIMENSIONS USED WITH MUELLER PACK JOINT COMPRESSION CONNECTION

Nominal Size	Material	Tubing or Pipe O.D. Range	Wall Thickness Range	Tubing or Pipe I.D. Range
1/2" CTS	CU (1)	0.622 - 0.628	0.045 - 0.053	-
3/4" CTS	CU (1)	0.872 - 0.878	0.061 - 0.069	-
	PE (2)	0.871 - 0.879	0.097 - 0.107	0.657 - 0.685
1" CTS	CU (1)	1.121 - 1.129	0.061 - 0.069	-
	PE (2)	1.120 - 1.130	0.125 - 0.137	0.846 - 0.880
1 - 1/4" CTS	CU (1)	1.371 - 1.379	0.060 - 0.070	-
	PE (2)	1.370 - 1.380	0.153 - 0.168	1.034 - 1.074
1 - 1/2" CTS	CU (1)	1.621 - 1.630	0.067 - 0.077	-
	PE (2)	1.619 - 0.181	0.181 - 0.199	1.221 - 1.269
2" CTS	CU (1)	2.120 - 2.130	0.076 - 0.090	-
	PE (2)	2.119 - 2.131	0.236 - 0.260	1.559 - 1.659
3/4" IPS	PE (3)	1.045 - 1.110	0.118 - 0.138	0.809 - 0.834
1" IPS	PE (3)	1.329 - 1.399	0.150 - 0.170	1.029 - 1.059

(1) Type "K" copper tubing – ASTM B88 (2) CTS polyethylene (PE) – ASTM D2737 SDR-9 (3) IPS polyethylene (PE) – ASTM D-2239 SDR-7

NOTE: Due to the characteristics of plastic pipe, it is necessary to use a rigid liner inside the end of the tubing or pipe.

3. DESIGN FEATURES

- 3.1 Connection parts are pre-assembled permitting piping to be stabbed into connection for fast, easy assembly, except for corporation valve use. For this use only it is necessary to remove the connection while corporation valve is inserted into the main or drilled through.
- 3.2 Nut bottoms on a shoulder eliminating need for torque wrench in assembly. This also provides visual final check to assure connection is properly aligned.
- 3.3 Sealing gasket has molded-in-place bronze spring (CTS only) to assure electrical contact for connection when used on metal tubing.
- 3.4 Sealing gasket is totally confined to prevent cold flow or creep either of which could cause future leakage.
- 3.5 Hardened Stainless Steel gripper band securely grips the pipe as its concave shape is compressed by the sealing gasket. This part provides the connection with high resistance to pull out, which could result from line pressure, back filling, ground settlement or accidental disturbance from ditching equipment.
- 3.6 Gripper band overlaps itself to prevent cold flow of the gasket into the cavity under the gripper band.
- 3.7 When this connection is used for plastic tubing or pipe, stainless steel continuous tube liners are used, which are flared at one end to prevent over-insertion into end of pipe.
- 3.8 The interior surface of the threads are coated with an anti-friction material to reduce assembly torque.
- 3.9 Mueller 110 Compression Connections are supplied as integral parts of a variety of waterworks products such as corporation valves, curb valves, meter valves, and meter setting materials, and as separate couplings and fittings.

For more information about us, or to view our full line of products, please visit www.muellerwp.com or call Mueller customer service at 1.800.423.1323.

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, Jones®, Krausz®, MiNet®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands to learn more.

© 2020 Mueller Water Products, Inc. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details visit www.mwppat.com.