



PARTS LIST					
ITEM	DESCRIPTION	REQ'D	MATERIAL	A.S.T.M.	
1	OPERATING NUT	1	BRONZE	B-62	C83600
2	WIPER RING	1	RUBBER	D-2000	R 33
3	HOLD DOWN NUT "O" RING	1	RUBBER	D-2000	R 34
4	HOLD DOWN NUT	1	BRONZE	B-62	C83600
5	BONNET "O" RING	1	RUBBER	D-2000	R 34
6	ANTI-FRICTION WASHER	1	PLASTIC		CELCON
7	OIL FILLER PLUG	1	BRASS	B-16	ALLOY 360
8	HOUSING	1	CAST IRON	A-126	CLASS B
9	HOUSING BOLT	6	STEEL	J429	GRADE 2 ZINC PLATED
10	WETHER CAP	1	CAST IRON	A-126	CLASS B
11	UPPER STEM	1	CARBON STEEL	A-567	GR. 1144T
12					
13	NOZZLE LOCK	3	STAINLESS STEEL	A-276	305 OR 410
14	PUMPER NOZZLE	1	BISMUTH BRASS	B-584	ALLOY C89833
15	PUMPER NOZZLE CAP GASKET	1	RUBBER	D-2000	R 51
16	PUMPER NOZZLE "O" RING	1	RUBBER	D-2000	R 34
17	PUMPER NOZZLE CAP	1	CAST IRON	A-126	CLASS B
18	HOSE NOZZLE	2	BISMUTH BRASS	B-584	ALLOY C89833
19	HOSE NOZZLE CAP GASKET	2	RUBBER	D-2000	R 51
20	HOSE NOZZLE "O" RING	2	RUBBER	D-2000	R 34
21	HOSE NOZZLE CAP	2	CAST IRON	A-126	CLASS B
22	CAP CHAIN	3	STEEL		ELECTRO GALV.
23	CHAIN HOOK	1	STEEL		ELECTRO GALV.
24	UPPER BARREL	1	CAST IRON	A-126	CLASS B
25	SAFETY STEM COUPLING	1	STAINLESS STEEL	A-890	GRADE 4A
26	SAFETY FLANGE BOLT	8	STEEL	J429	GRADE 2 ZINC PLATED
27	BOTTOM UPPER BARREL O-RING	1	RUBBER	D-2000	BUNA N
28	SAFETY FLANGE	1	CAST IRON	A-126	CLASS B
29	COTTER PIN	2	STAINLESS STEEL	A-276	302
30	CLEVIS PIN	2	STAINLESS STEEL	A-276	305
31	LOWER STEM	1	CARBON STEEL	A-567	GR. 1144T
32	LOWER BARREL	1	CAST IRON	A-126	CLASS B
33	STEM PIN	1	STAINLESS STEEL	A-276	302
34	DRAIN VALVE FACING	2	PLASTIC		H.D. POLYETHYLENE
35	DRAIN VALVE FACING SCREW	4	STAINLESS STEEL	A-276	302
36	UPPER VALVE PLATE	1	BISMUTH BRASS	B-584	ALLOY C89833
37	BOTTOM SEAT "O" RING	1	RUBBER	D-2000	R 34
38	DRAIN RING HOUSING	1	CAST IRON	A-126	CLASS B
39	SEAT RING	1	BISMUTH BRASS	B-584	ALLOY C89833
40	DRAIN RING	1	BRONZE	B-62	C83600
41	MAIN VALVE	1	RUBBER	D-2000	R-44
42	LOWER VALVE PLATE	1	CAST IRON	A-126	CLASS B
43	LOCK WASHER	1	STAINLESS STEEL	A-276	302
44	VALVE NUT	1	CAST IRON	A-126	CLASS B
45	VALVE NUT SEAL	1	RUBBER		R-32
* 46	PIPE PLUG	1			
47	HOUSING O-RING	2	RUBBER		R-34
48	SAFETY FLANGE NUT	8	STEEL	A-563	GRADE B ZINC PLATED
49	SAFETY STEM COUP. PIN	1	STEEL		MIL-P-10971A
50					
51	UPPER STEM PIN	1	STAINLESS STEEL	A-276	302
52	HEX BOLT	6	STEEL	J429	GRADE 2 ZINC PLATED
53	SHOE	1	DUCTILE IRON	A-536	65-45-12
54	PIPE GLAND	1	CAST IRON	A-126	CLASS B
55	SEAL	1	RUBBER	D-2000	R 34
56	"O" RING	1	RUBBER	D-2000	R 34
57	HEX NUT	6	STEEL	A-563	GRADE B ZINC PLATED

SEE CAT. RECORD FOR RESPECTIVE PARTS OR SUB. ASS'YS
 * OPTIONAL

(MILLIMETER) INCH INITIAL RELEASE DRFT'R ANC 18-13-15 CHK'R APP E.O. NUMBER	TOLERANCES - MACHINING UNLESS OTHERWISE NOTED BREAK EDGES MACH. .006/.016 FINISH SURFACES 125 FRACTIONS ±1/64 DECIMALS 2 PL ±.025 3 PL ±.010 ANGLES ±1°	THIRD ANGLE PROJECTION PURCH. FINISH REF. NO. SCALE N.T.S. STK. NO.
MAT'L SEE TABLE DESC'R A-444 5-1/4 MODERN (1997 DESIGN) UNDERWRITER ASSEMBLY		REVISION NUMBER - FH-609 SHEET 1 OF 1