



No.	DESCRIPTION	MATERIAL
1	BODY	CAST LOW LEAD BRASS ALLOY
2	KEY	CAST LOW LEAD BRASS ALLOY
3	KEY INSERT	ABS CYCOLAC MG47N PLASTIC
4	COUP. NUT	CAST BRASS ASTM B62 ALLOY C83600
5	TOP SEAL	RUBBER
6	RETAINING RING	BRONZE ASTM B103 ALLOY C52100
7	THRUST WASHER	CELCON M90 PLASTIC
8	O-RING	RUBBER ASTM D-2000 EPDM
9	O-RING	RUBBER ASTM D-2000 EPDM
10	CTS GSKT SUB	SBR D2000 - GSKT 410ss - BAND

SIZE	A	B	C
3/4	4.38	1.94	3.18
1	4.00	2.16	3.60

NOTE: ALL WETTED PARTS ARE LOW LEAD BRASS ALLOY

FILEPATH: PROD-ENG\MUELLER\ASYSUBMITTALS\H1504-2N

DRFTR	RWB	4/12/13		THIRD ANGLE PROJECTION 	
CHKR					
ENGR					
MGR					
	BY	DATE	UNLESS OTHERWISE NOTED	REF. No.	SCALE
			SURFACE PREPARATION:		NONE
			BREAK CORNER(S) ---- .000		
			SURFACE FINISH -- XX RMS		
			TOLERANCE(S):		
			LINEAR ----- ± .000		
			ANGULAR ----- ± 0°00'		
			STK No:		
			MAT'L:		
			DESCR.		
			DRISEAL III LLB CURB VALVE		DWG NUMBER
			(110 CTS x 110 CTS)		H1504-2N
REV	ECR	DESCRIPTION	DATE	BY	CHKR
PER EST NO: DXXXX EST FIN WT = 0.0000 lbs					

DWG NUMBER
H1504-2N
442-MRKTG

TITLE TO AND OWNERSHIP OF THIS ENGINEERING DATA REMAINS IN Mueller Co. NO USE IS TO BE MADE OF THIS DATA EXCEPT AS SPECIFICALLY AUTHORIZED BY Mueller Co. ASSENT ON THE PART OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED