



No.	DESCRIPTION	MATERIAL
1	BODY	CAST LOW LEAD BRASS ALLOY
2	CAP	CAST BRASS ASTM B62 ALLOY C83600
3	STEM	LOW LEAD BRASS ALLOY
4	ROLL PIN	STAINLESS STEEL
5	O-RING	EPDM ASTM D2000
6	GASKET - SEAL	NITRILE ASTM D2000
7	BALL	LOW LEAD BRASS ALLOY
8	O-RING	EPDM ASTM D2000
9	O-RING	EPDM ASTM D2000
10	END PIECE	CAST LOW LEAD BRASS ALLOY
11	PJ GASKET	ASTM D2000 (BUNA N)
12	PJ WASHER	POLYPROPYLENE
13	PJ CPLG NUT	CAST BRASS ASTM B62 ALLOY C83600

SIZE	A	B	C	D
1"	1.00	4.92	1.15	2.84
1-1/2"	1.50	5.50	1.66	3.46
2"	2.00	6.59	1.82	3.78

ALL WETTED PARTS ARE LOW LEAD BRASS ALLOY

FILEPATH: PRODD-ENG\MUELLER\ASYSUBMITTALS\V25112N

DRFTR	RWB	3/14/17	Mueller Co.		
CHKR					
ENGR					
MGR					
UNLESS OTHERWISE NOTED			THIRD ANGLE PROJECTION		
SURFACE PREPARATION:					
BREAK CORNER(S) ---- .000					
SURFACE FINISH -- XX RMS			REF. No.		
TOLERANCE(S):			SCALE		
LINEAR ----- ± .000			FULL		
ANGULAR ----- ± 0°00'					
BY DATE					
STK No:					
MAT'L:					
DESCR.			DWG NUMBER		
INLINE LLB DRAINING BALL VALVE MINN. TOP			V25112N		
PVC-PJ x PVC-PJ					
REV	ECR	DESCRIPTION	DATE	BY	CHKR
PER EST NO: DXXXX EST FIN WT = 0.0000 lbs					

DWG NUMBER
V25112N
442-MRKTG

TITLE TO AND OWNERSHIP OF THIS ENGINEERING DATA REMAINS IN Mueller Co. NO USE IS TO BE MADE OF THIS DATA EXCEPT AS SPECIFICALLY AUTHORIZED BY Mueller Co. ASSENT ON THE PART OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED.