

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

## SECTION 1. IDENTIFICATION

Product name : ALEXIT-Monolyer® 402-4B 31AQ Mueller Red / 10 F63RL15  
glänzend / high gloss

Product code : 4024B31AQ9000

### Manufacturer or supplier's details

Manufacturer, importer,  
supplier Mankiewicz Coatings L.L.C

Address 1200 Charleston Regional Parkway  
Charleston, South Carolina 29492  
USA

Telephone +1 (843) 6547755

E-mail address sdb\_info@umco.de

Emergency telephone USA Toll free +1 866 928 0789 EN/FR/ES(Carechem Interna-  
tional)  
Canada Toll free +1 800 579 7421 EN/FR (Carechem Interna-  
tional)

### Recommended use of the chemical and restrictions on use

Recommended use : Industrial serial painting

## SECTION 2. HAZARDS IDENTIFICATION

### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Skin sensitization : Category 1

Carcinogenicity : Category 1A

Reproductive toxicity : Category 1B

Specific target organ toxicity : Category 2  
- repeated exposure



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

## GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.  
H317 May cause an allergic skin reaction.  
H350 May cause cancer.  
H360FD May damage fertility. May damage the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe mist or vapors.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

## Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

## Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

## Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture of synthetic resins, organic solvents and pigments

### Components

Chemical name	CAS-No.	Concentration (% w/w)
n-butyl acetate	123-86-4	>= 5 - < 12.5
2-butoxyethyl acetate	112-07-2	>= 5 - < 12.5
2-methoxy-1-methylethyl acetate	108-65-6	>= 5 - < 12.5
titanium dioxide	13463-67-7	>= 1 - < 5
Hydrocarbons, C9, aromatics	64742-95-6	>= 1 - < 5
xylenes	1330-20-7	>= 1 - < 5
ethylbenzene	100-41-4	>= 0.5 - < 1
Naphtha (petroleum), heavy alkylate	64741-65-7	>= 0.25 - < 0.5
dibutyltin dilaurate	77-58-7	>= 0.1 - < 0.25
ethanol	64-17-5	>= 0.1 - < 0.25
quartz (SiO <sub>2</sub> )	14808-60-7	>= 0.1 - < 0.25

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

If inhaled : Remove to fresh air, keep patient warm and at rest.  
Irregular breathing/no breathing: artificial respiration.  
If unconscious place in recovery position and seek medical advice.

In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognised



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

- skin cleanser.  
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.  
If accidentally swallowed obtain immediate medical attention.  
Never give anything by mouth to an unconscious person.  
Keep at rest.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
May cause cancer.  
May damage fertility. May damage the unborn child.  
May cause damage to organs through prolonged or repeated exposure.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Further information : Cool endangered containers with water in case of fire.  
**DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!**
- Special protective equipment for fire-fighters : As in any fire, wear self-contained breathing apparatus pressure - demand, MSHA / NIOSH (approved or equivalent) and full protective gear.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Exclude sources of ignition and ventilate the area.  
Do not inhale vapors.  
Refer to protective measures listed in sections 7 and 8.  
Evacuate personnel to safe areas.
- Environmental precautions : Do not let product enter drains.  
If the product contaminates lakes, rivers or sewage, inform



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

appropriate authorities in accordance with local regulations.

Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).  
Clean preferably with a detergent; avoid use of solvents.

## SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
Preparation may charge electrostatically: always use earthing leads when transferring from one container to another.  
Operators should wear anti-static footwear and clothing. No sparking tools should be used.  
Vapors are heavier than air and may spread along floors.  
Vapors may form explosive mixtures with air.

Advice on safe handling : Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentrations higher than the occupational exposure limits.  
Comply with the health and safety at work laws.  
Smoking, eating and drinking should be prohibited in the application area.  
Observe specific national regulations for handling and use of paints.

Conditions for safe storage : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type.  
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.  
Keep container dry in a cool, well-ventilated place.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
 Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

Recommended storage temperature : 41 - 95 °F / 5 - 35 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		STEL	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		VLE-PPT	150 ppm	NOM-010-STPS-2014
		VLE-CT	200 ppm	NOM-010-STPS-2014
		TWA	150 ppm 710 mg/m <sup>3</sup>	NIOSH REL
		ST	200 ppm 950 mg/m <sup>3</sup>	NIOSH REL
		TWA	150 ppm 710 mg/m <sup>3</sup>	OSHA Z-1
		TWA	150 ppm 710 mg/m <sup>3</sup>	OSHA P0
		STEL	200 ppm 950 mg/m <sup>3</sup>	OSHA P0
		TWA	50 ppm	ACGIH
STEL	150 ppm	ACGIH		
2-butoxyethyl acetate	112-07-2		1,000 ml/m <sup>3</sup> 2,400 mg/m <sup>3</sup>	LIMITS FOR AIR CONTAMINANTS (OSHA)
			20 ml/m <sup>3</sup>	ACGIH
		TWA	20 ppm 131 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		VLE-PPT	20 ppm	NOM-010-STPS-2014
		TWA	20 ppm	ACGIH
		TWA	5 ppm 33 mg/m <sup>3</sup>	NIOSH REL
		TWAEV	20 ppm	CA QC OEL



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
 Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m3	CA ON OEL
		TWA	50 ppm	US WEEL
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
Hydrocarbons, C9, aromatics	64742-95-6	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
xylenes	1330-20-7	VLE-PPT	100 ppm	NOM-010-STPS-2014
		VLE-CT	150 ppm	NOM-010-STPS-2014
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	20 ppm	ACGIH
		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWA	100 ppm 434 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
 Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

		STEL	150 ppm	CA BC OEL
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	125 ppm 543 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		VLE-PPT	20 ppm	NOM-010- STPS-2014
		TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	CA AB OEL
		STEL	0.2 mg/m3 (Tin)	CA AB OEL
		TWAEV	0.1 mg/m3 (Tin)	CA QC OEL
		STEV	0.2 mg/m3 (Tin)	CA QC OEL
		TWA	0.1 mg/m3 (Tin)	CA BC OEL
		STEL	0.2 mg/m3 (Tin)	CA BC OEL
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3	CA ON OEL





# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
 Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

			(Tin)	
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
		VLE-PPT	0.1 mg/m3 (Tin)	NOM-010- STPS-2014
		VLE-CT	0.2 mg/m3 (Tin)	NOM-010- STPS-2014
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		VLE-CT	1,000 ppm	NOM-010- STPS-2014
		STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEV	1,000 ppm	CA QC OEL
quartz (SiO2)	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		VLE-PPT (Respirable fraction)	0.025 mg/m3	NOM-010- STPS-2014
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
 Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylenes	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
		Methyl-hippuric acid	Urine	End of shift	1.5 g/g creatinine	MX BEI
ethylbenzene	100-41-4	Sum of Mandelic acid plus phenylglyoxylic acid	Urine	End of shift at end of work-week	0.7 g/g creatinine	MX BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

**Engineering measures** : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapors concentration below the OEL, suitable respiratory protection must be worn.

### Personal protective equipment

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Use MSHA/NIOSH approved respirator if concentration exceeds recommended exposure levels. Dry grinding, torch cutting and/or welding however can produce hazardous dust and/or vapor.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

If possible, machine employing a wet medium.  
Where practicable, install exhaust hoods to improve capture of vapors and fumes and avoid exposition; otherwise wear respiratory protection equipment.

## Hand protection

Remarks : Glove permeation data does not exist for this material.  
The following glove(s) should be used for splash protection only:  
Appropriate material: nitrile

Eye protection : Use safety glasses or face shield (ANSI Z87.1 or approved equivalent).

Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.

Protective measures : Do not eat or drink during work - no smoking.  
Avoid product contact with skin, eyes and clothing.  
Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapor in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapor concentration has fallen below the exposure limits.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid (68 - 77 °F / 20 - 25 °C, 1,013 hPa)

Color : according product name

Odor : characteristic

pH : substance/mixture is non-soluble (in water)



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

	: No data available
Boiling point/boiling range	: ca. 248 °F / 120 °C
Flash point	: 82 °F / 28 °C Method: ISO 13736
Flammability (liquids)	: No data available
Upper explosion limit / Upper flammability limit	: 10 %(V)
Lower explosion limit / Lower flammability limit	: 1 %(V)
Vapor pressure	: ca. 100 hPa (122 °F / 50 °C)
Relative density	: No data available
Density	: ca. 10.8 lb/gal (1.3 g/cm <sup>3</sup> ) (68 °F / 20 °C)
Solubility(ies) Water solubility	: insoluble
Autoignition temperature	: > 752 °F / > 400 °C
Decomposition temperature	: No data available
Viscosity Viscosity, kinematic	: > 21 mm <sup>2</sup> /s
Flow time	: 95 s Cross section: 4 mm Method: DIN 53211  63 s Cross section: 6 mm Method: ISO 2431

## SECTION 10. STABILITY AND REACTIVITY



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use. There are no data available on the preparation itself.
- Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).
- Incompatible materials : Keep away from oxidizing agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.
- Hazardous decomposition products : When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Not classified due to lack of data.

### Product:

- Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method
- Acute inhalation toxicity : Acute toxicity estimate: 137.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Components:

#### **2-butoxyethyl acetate:**

- Acute oral toxicity : LD50 (Rat): 1,880 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): 1,480 mg/kg

#### **dibutyltin dilaurate:**



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

Acute oral toxicity : LD50 (Rat): 2,071 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

### Skin corrosion/irritation

Not classified due to lack of data.

### Serious eye damage/eye irritation

Not classified due to lack of data.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified due to lack of data.

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

May cause cancer.

<b>IARC</b>	Group 1: Carcinogenic to humans ethanol	64-17-5
	Group 1: Carcinogenic to humans quartz (SiO <sub>2</sub> ) (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
	Group 2B: Possibly carcinogenic to humans Naphtha (petroleum), heavy alkylate (gasoline)	64741-65-7

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** Known to be human carcinogen  
quartz (SiO<sub>2</sub>) 14808-60-7  
(Silica, Crystalline (Respirable Size))

### Reproductive toxicity

May damage fertility. May damage the unborn child.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

## STOT-single exposure

Not classified due to lack of data.

## STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

## Aspiration toxicity

Not classified due to lack of data.

## Further information

### Product:

Remarks : Exposure of vapor concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

#### Components:

#### Hydrocarbons, C9, aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 2.9



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

plants mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

## Persistence and degradability

### Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

## Bioaccumulative potential

### Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

## Mobility in soil

### Product:

Mobility : Remarks: There are no data available on the preparation itself.

## Other adverse effects

### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water courses.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.





# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

#### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT  
(trizinc bis(orthophosphate), dibutyltin dilaurate)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
Marine pollutant : yes(trizinc bis(orthophosphate), dibutyltin dilaurate)



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
1.12	01/12/2024	F-4024B31AQ9	Date of first issue: 03/13/2023

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Respiratory or skin sensitization  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-butoxyethyl acetate	112-07-2	>= 5 - < 10 %
trizinc bis(orthophosphate)	7779-90-0	>= 1 - < 5 %
xylenes	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %
zinc oxide	1314-13-2	>= 0.1 - < 1 %

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

xylenes	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermedi-ate or Final VOC's (40 CFR 60.489):

n-butyl acetate	123-86-4	>= 10 - < 20 %
2-butoxyethyl acetate	112-07-2	>= 5 - < 10 %
xylenes	1330-20-7	>= 1 - < 5 %

VOC content excluding water : 2.98 lb/gal (358 g/l)

For the calculation of VOC values in this section all substances have been considered which fall under the definition of VOC according to 40 CFR 51.100. Additionally, the calculation complies with the requirements of SCAQMD Rule 1106.1, amended February 12, 1999.

## Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Ta-ble 116.4A:

n-butyl acetate	123-86-4	>= 10 - < 20 %
xylenes	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %
1,2-dichlorobenzene	95-50-1	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

n-butyl acetate	123-86-4	>= 10 - < 20 %
xylenes	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

trizinc bis(orthophosphate)	7779-90-0	>= 1 - < 5 %
-----------------------------	-----------	--------------

This product does not contain any priority pollutants related to the U.S. Clean Water Act

## US State Regulations

### Massachusetts Right To Know

n-butyl acetate	123-86-4
xylenes	1330-20-7
quartz (SiO <sub>2</sub> )	14808-60-7

### Pennsylvania Right To Know

n-butyl acetate	123-86-4
2-butoxyethyl acetate	112-07-2
trizinc bis(orthophosphate)	7779-90-0
Hydrocarbons, C9, aromatics	64742-95-6
xylenes	1330-20-7
ethylbenzene	100-41-4
zinc oxide	1314-13-2
aluminium oxide (Smoke)	1344-28-1

### Maine Chemicals of High Concern



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

quartz (SiO<sub>2</sub>) 14808-60-7

### Vermont Chemicals of High Concern

ethylbenzene 100-41-4  
quartz (SiO<sub>2</sub>) 14808-60-7  
butanone 78-93-3

### Washington Chemicals of High Concern

ethylbenzene 100-41-4  
quartz (SiO<sub>2</sub>) 14808-60-7  
butanone 78-93-3

### California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, ethanol, quartz (SiO<sub>2</sub>), which is/are known to the State of California to cause cancer, and ethanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California List of Hazardous Substances

n-butyl acetate 123-86-4  
trizinc bis(orthophosphate) 7779-90-0  
xylenes 1330-20-7

### California Permissible Exposure Limits for Chemical Contaminants

n-butyl acetate 123-86-4  
2-methoxy-1-methylethyl acetate 108-65-6  
titanium dioxide 13463-67-7  
xylenes 1330-20-7

### California Regulated Carcinogens

quartz (SiO<sub>2</sub>) 14808-60-7

### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

## SECTION 16. OTHER INFORMATION

### Further information



# SAFETY DATA SHEET


according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version 1.12	Revision Date: 01/12/2024	SDS Number: F-4024B31AQ9	Date of last issue: 11/01/2023 Date of first issue: 03/13/2023
-----------------	------------------------------	-----------------------------	---

## NFPA 704:



## HMIS® IV:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Health  
0=Slightly Hazardous  
2=Hazardous  
3=Extreme danger  
4=Deadly

Flammability  
0=Will not burn  
2=Flashpoint below 200 F  
3=Flashpoint below 100 F  
4=Flashpoint below 73 F

Instability  
0=Stable  
1=Unstable if heated  
2=Violent chemical reaction; water reactive  
3=Shock or heat may detonate  
4=May detonate

Special hazard  
SA Simple Asphyxiant  
ACID Acid  
OX Oxidizer  
W Water Reactive  
CORR Corrosive

## Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
1.12	01/12/2024	F-4024B31AQ9	Date of first issue: 03/13/2023

CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
MX BEI	:	Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices for workers occupationally exposed to chemical agents
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
NOM-010-STPS-2014	:	Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NOM-010-STPS-2014 / VLE-PPT	:	Time weighted average limit value
NOM-010-STPS-2014 / VLE-CT	:	Short term exposure limit value
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average
US WEEL / TWA	:	8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
1.12	01/12/2024	F-4024B31AQ9	Date of first issue: 03/13/2023

German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law.

Adhere to the national sanitary and occupational safety regulations when using this product. This SDS have been created to comply with The Hazard Communication Standard (HCS)(29 CFR 1910.1200).

This SDS have been created to comply with the Hazardous Products Regulations(SOR/2015-17).

Revision Date : 01/12/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXIT-Monolyer® 402-4B  
Product No.: 4024B31AQ9000

---

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
1.12	01/12/2024	F-4024B31AQ9	Date of first issue: 03/13/2023

---

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8

