


No.	DESCRIPTION	MATERIAL
1	STEM	LEAD FREE BRASS ALLOY ASTM B584/B371
2	O-RING	EPDM D2000
3	BALL	LEAD FREE BRASS ALLOY NICR PLATED
4	GASKET - SEAL	EPDM D2000
5	BODY	LEAD FREE BRASS ALLOY ASTM B584
6	O-RING	EPDM D2000
7	END PIECE	LEAD FREE BRASS ALLOY ASTM B584
8	CAP	CAST BRASS ALLOY ASTM B584
9	SCREW	410 STAINLESS STEEL

MEETS ALL REQUIREMENTS OF AWWA C800
ALL STEMS ARE LEAD FREE BRASS ALLOY C89833/C69300
ALL WETTED PARTS ARE LEAD FREE BRASS ALLOY C89833/C87850
ALL NON WETTED PARTS ARE BRASS ALLOY C83600/C87850

SIZE	ØA	B	C	D
1"	1.00	3.97	2.91	4.06
1-1/2"	1.50	4.31	3.46	4.96
2"	2.00	4.96	3.77	5.94



DRFTR	RWB	6/2/25	MUELLER	
CHKR				
ENGR			UNLESS OTHERWISE NOTED SURFACE PREPARATION: BREAK CORNER(S) ---- .000 SURFACE FINISH -- XX RMS TOLERANCE(S): LINEAR ----- ± .000 ANGULAR ----- ± 0°00'	THIRD ANGLE PROJECTION
MGR				REF. No.
	BY	DATE		SCALE
				NONE
STK No:			MAT'L:	
DESCR.			DWG NUMBER	
INLINE MINN TOP DRAINING BALL VALVE FIP x FIP			B20288	

DWG NUMBER
B20288

TITLE TO AND OWNERSHIP OF THIS ENGINEERING
DATA REMAINS IN Mueller Co. NO USE IS TO BE
MADE OF THIS DATA EXCEPT AS SPECIFICALLY
AUTHORIZED BY Mueller Co. ASSENT ON THE PART
OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED