




No.	DESCRIPTION	MATERIAL
1	STEM	LEAD FREE BRASS ALLOY ASTM B584/B371
2	O-RING	EPDM D2000
3	BALL	LEAD FREE BRASS ALLOY ASTM B584
4	GASKET - SEAL	EPDM D2000
5	BODY	LEAD FREE BRASS ALLOY ASTM B584
6	O-RING	EPDM D2000
7	END PIECE	LEAD FREE BRASS ALLOY ASTM B584
8	CAP	CAST BRASS ALLOY ASTM B584
9	SOLID PIN	AISI 303 STAINLESS STEEL

SIZE	øA	B	C	D	E
3/4R	.625	1.477	1.656	2.120	3.776
3/4	.750	1.789	1.656	2.323	3.979
1R	.750	1.718	2.031	2.323	4.354
1	1.000	2.066	2.031	2.617	4.648

MEETS ALL REQUIREMENTS OF AWWA C800
ALL STEMS ARE LEAD FREE BRASS ALLOY C89833/C69300
ALL WETTED PARTS ARE LEAD FREE BRASS ALLOY C89833/C87850
ALL NON WETTED PARTS ARE BRASS ALLOY C83600/C87850

DRFTR	RWB	4/3/15	MUELLER	
CHKR				
ENGR			UNLESS OTHERWISE NOTED SURFACE PREPARATION: BREAK CORNER(S) ---- .000 SURFACE FINISH -- XX RMS TOLERANCE(S): LINEAR ----- ± .000 ANGULAR ----- ± 0°00'	THIRD ANGLE PROJECTION
MGR				REF. No.
	BY	DATE		SCALE NONE
STK No:			MAT'L:	
DESCR.			ANGLE METER BALL VALVE (FIP x FIP)	
			DWG NUMBER B24285N	

DWG NUMBER
B24285N

TITLE TO AND OWNERSHIP OF THIS ENGINEERING
DATA REMAINS IN Mueller Co. NO USE IS TO BE
MADE OF THIS DATA EXCEPT AS SPECIFICALLY
AUTHORIZED BY Mueller Co. ASSENT ON THE PART
OF THE RECIPIENT TO THESE CONDITIONS IS PRESUMED