

MILLIKEN®

a MUELLER brand

MILLCENTRIC® PLUG VALVE

PRODUCT FEATURES

The Milliken Millcentric 2-Way Plug Valve is used for the isolation and control of a wide range of applications from Water and Wastewater to slurries, powder, air and other mediums. The Milliken Millcentric Plug Valve carries the normal Milliken quality, value and reliability.

- ½" (DN15) – 72" (DN1800).
- Conforms to AWWA C517.
- Available flanged to EN1092-2 PN10/16/25, AS2129/4087 PN16/21, ANSI B16.1 Class 125.
- Wide variety of Plug Elastomers to suit a range of applications.
- Fusion Bonded Epoxy (FBE) Coated as standard.
- Can be used for Isolation and/or Flow Control.
- Welded Nickel Seat for durability.
- Manual, Gear or Motor operated.
- Bi-directional.
- Ductile Iron and Stainless Steel versions available.



DIMENSIONS – THREADED ENDS PN16 - INCHES (MM)

VALVE SIZE	A-NPT	B	C	D	E	F	WEIGHT- LBS (KG)
½"/DN15	½ (13)	2⅛ (54)	1⅞ (48)	4⅜ (111)	1⅜ ₁₆ (46)	2 (51)	6.6 (3.02)
¾"/DN20	¾ (19)	2⅛ (54)	1⅞ (48)	4⅜ (111)	1⅜ ₁₆ (46)	2 (51)	6.5 (2.97)
1"/DN25	1 (25)	2⅛ (54)	1⅞ (48)	4⅜ (111)	1⅜ ₁₆ (46)	2 (51)	6.4 (2.92)
1¼"/DN35	1¼ (32)	3 (76)	2½ (64)	5 (127)	2½ (64)	2 (51)	11.7 (5.32)
1½"/DN40	1½ (38)	3 (76)	2½ (64)	5 (127)	2½ (64)	2 (51)	11.5 (5.22)
2"/DN50	2 (51)	3 (76)	2½ (64)	5 (127)	2½ (64)	2 (51)	10.9 (4.96)

Note:

Drawings are for information purposes only; please request certified drawings before preparing piping drawings.


- BSP taper threaded ends available to order and subject to minimum quantities.



MUELLER


DIMENSIONS – FLANGED END PN10/16 INCHES (MM)

VALVE SIZE	A	B	C	E	F	ØG
2½" (DN65)	7 (178)	¾ (20)	7½ (191)	3¾ (89)	5½ (137)	6 (152)
3" (DN80)	7½ (191)	⅞ (22)	8 (203)	3¾ (95)	5½ (142)	6 (152)
4" (DN100)	9 (229)	1⅝ (24)	9 (229)	4½ (114)	6¼ (160)	6 (152)
5" (DN125)	10 (254)	1⅞ (26)	10 (254)	5¾ (146)	7⅞ (192)	6 (152)
6" (DN150)	11 (279)	1⅞ (26)	10½ (267)	5¾ (146)	7⅞ (192)	6 (152)
8" (DN200)	13½ (343)	1⅞ (30)	11½ (292)	7⅞ (194)	9⅞ (245)	12 (305)
10" (DN250)	16 (406)	1⅞ (32)	13 (330)	8⅞ (226)	11⅞ (295)	12 (305)
12" (DN300)	19 (483)	1⅞ (32)	14 (356)	10 (254)	13⅞ (338)	12 (305)
14" (DN350)	21 (533)	1⅞ (35)	17 (432)	13 (330)	15 (381)	18 (457)
16" (DN400)	23 (591)	1⅞ (36)	17¾ (451)	14 (356)	15⅞ (402)	18 (457)
18" (DN450)	25 (635)	1⅞ (40)	21½ (546)	15 (381)	17 (432)	18 (457)
20" (DN500)	27½ (699)	1⅞ (43)	23½ (597)	16 (406)	20⅞ (519)	18 (457)
24" (DN600)	32 (813)	1⅞ (48)	42 (1067)	21⅞ (549)	22⅞ (581)	24 (610)
28" (DN700)	38¾ (984)	2⅞ (54)	51 (1295)	24¾ (629)	27⅞ (701)	24 (610)
32" (DN800)	38¾ (984)	2⅞ (60)	51 (1295)	24¾ (629)	27⅞ (701)	24 (610)
36" (DN900)	46 (1168)	2⅞ (67)	60 (1524)	29 (737)	33 (838)	24 (610)
40" (DN1000)	53 (1346)	2⅞ (67)	72 (1829)	29 (737)	37⅞ (956)	30 (762)



DIMENSIONS – FLANGED END PN25 INCHES (MM)

VALVE SIZE	A	B	C	E	F	ØG
2½" (DN65)	7½ (191)	1⅞ (27)	9½ (241)	3½ (89)	6 (152)	6 (152)
3" (DN80)	8¼ (210)	1⅞ (28)	11⅞ (282)	3¾ (95)	6⅞ (175)	6 (152)
4" (DN100)	10 (254)	1⅞ (32)	12 (305)	4½ (114)	7 (178)	6 (152)
5" (DN125)	11 (279)	1⅞ (35)	15 (381)	5¾ (146)	8⅞ (211)	6 (152)
6" (DN150)	12½ (318)	1⅞ (36)	15⅞ (402)	5¾ (146)	8⅞ (211)	6 (152)
8" (DN200)	15 (381)	1⅞ (41)	16½ (419)	8¼ (210)	10⅞ (257)	12 (305)
10" (DN250)	17½ (445)	1⅞ (48)	18 (457)	8⅞ (226)	13⅞ (353)	12 (305)
12" (DN300)	20½ (521)	2 (51)	19¾ (502)	10 (254)	14¾ (375)	12 (305)
14" (DN350)	23 (584)	2⅞ (54)	18½ (470)	13 (330)	15⅞ (383)	18 (457)
16" (DN400)	25½ (648)	2⅞ (57)	19⅞ (492)	14 (356)	15⅞ (402)	18 (457)
18" (DN450)	28 (711)	2⅞ (60)	23⅞ (587)	15 (381)	17 (432)	18 (457)
20" (DN500)	30½ (775)	2⅞ (63)	25 (635)	16 (406)	20⅞ (519)	18 (457)
24" (DN600)	36 (914)	2⅞ (70)	42⅞ (1089)	21⅞ (549)	22⅞ (581)	24 (610)
28" (DN700)	43 (1092)	3 (76)	51⅞ (1318)	24¾ (629)	27⅞ (701)	24 (610)
32" (DN800)	43 (1092)	3 (76)	51⅞ (1318)	24¾ (629)	27⅞ (701)	24 (610)
36" (DN900)	50 (1270)	3⅞ (86)	61 (1549)	29 (737)	33 (838)	24 (610)
40" (DN1000)	52 (1320)	2⅞ (63)	72 (1829)	29 (737)	37⅞ (956)	30 (762)



WEIGHT - LBS (KG)

VALVE SIZE	2" (DN50)	2½" (DN65)	3" (DN80)	4" (DN100)	5" (DN125)	6" (DN150)	8" (DN200)	10" (DN250)	12" (DN300)
Flanged Ends - PN10/16	18 (8.2)	31 (14)	40 (18)	70 (32)	106 (48)	115 (52)	190 (86)	344 (156)*	441 (200)*
Flanged Ends - PN25	-	40 (18)	79 (36)	119 (54)	161 (73)	170 (77)	275 (125)	399 (181)	591 (268)

VALVE SIZE	14" (DN350)	16" (DN400)	18" (DN450)	20" (DN500)	24" (DN600)	28" (DN700)	32" (DN800)	36" (DN900)	40" (DN1000)
Flanged Ends - PN10/16	906 (411)	1030 (467)	1356 (615)	1880 (853)	3801 (1724)	5201 (2359)	5201 (2359)	6951 (3153)	10161 (4609)
Flanged Ends - PN25	981 (445)	1124 (510)	1389 (630)	2055 (934)	4160 (1887)	5701 (2586)	5701 (2586)	7670 (3479)	9845 (4475)

Note:

Drawings are for information purposes only; please request certified drawings before preparing piping drawings.

- DN250 and larger have gear operator as standard.
- Dimensions for DN1000 and larger available on request.

* Weight includes gear operator

For more information about us, or to view our full line of products, please visit www.mueller-international.com or call International Customer Service at:

UK: +44.1438.487410 Dubai: +971.4.214.6640 Singapore: +65.6816.3088 USA: +1.800.423.1323 | International@muellerwp.com

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, Jones®, Kraus®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands to learn more.

© 2020 Mueller Water Products, Inc. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details visit www.muellerwp.com.

F 12993 3/20

MUELLER